

ISO 18582-2:2018 (E)

Fluid power — Specification of reference dictionary — Part 2: Definitions of classes and properties of pneumatics

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	General principles
5	Definition class: fluid systems and components for general use, 18582#KAA001-001-001
6	Properties
6.1	18582#KAA002-001-001: initial value of pressure measuring range
6.2	18582#KAA003-001-001: shifting-on time
6.3	18582#KAA004-001-001: condensate drain connection
6.4	18582#KAA005-001-001: number of pneumatic connections
6.5	18582#KAA006-001-001: number of pneumatic output connections
6.6	18582#KAA007-001-001: number of pneumatic input connections
6.7	18582#KAA008-001-001: number of pneumatic exhaust connections
6.8	18582#KAA009-001-001: number of pneumatic pilot ports
6.9	18582#KAA010-001-001: type of cushioning
6.10	18582#KAA011-001-001: type of stroke reduction
6.11	18582#KAA012-001-001: type of pneumatic connections
6.12	18582#KAA013-001-001: type of shaft end
6.13	18582#KAA014-001-001: shifting-off time
6.14	18582#KAA015-001-001: size
6.15	18582#KAA016-001-001: actuation type
6.16	18582#KAA017-001-001: operating pressure for max. vacuum
6.17	18582#KAA018-001-001: moving mass
6.18	18582#KAA019-001-001: moving mass with 0 mm stroke
6.19	18582#KAA020-001-001: moving mass per 10 mm stroke
6.20	18582#KAA021-001-001: critical back-pressure ratio
6.21	18582#KAA022-001-001: sonic conductance C
6.22	18582#KAA023-001-001: cushioning length
6.23	18582#KAA024-001-001: cushioning angle
6.24	18582#KAA025-001-001: continuous load factor
6.25	18582#KAA026-001-001: sealing principle
6.26	18582#KAA027-001-001: seal on threaded plug
6.27	18582#KAA028-001-001: torque at 6 bar
6.28	18582#KAA029-001-001: compressed air quality class at outlet
6.29	18582#KAA030-001-001: compressed air quality class at inlet
6.30	18582#KAA031-001-001: pressure medium
6.31	18582#KAA032-001-001: suitability for both directions of flow
6.32	18582#KAA033-001-001: final value of pressure measuring range
6.33	18582#KAA034-001-001: grade of filtration
6.34	18582#KAA035-001-001: filter efficiency
6.35	18582#KAA036-001-001: function in normal position
6.36	18582#KAA037-001-001: mode of operation of drive
6.37	18582#KAA038-001-001: noise reduction
6.38	18582#KAA039-001-001: graphic symbol

6.39 18582#KAA040-001-001: number of gripper fingers
 6.40 18582#KAA041-001-001: gripping force with external gripping
 6.41 18582#KAA042-001-001: gripping force with internal gripping
 6.42 18582#KAA043-001-001: gripping torque with external gripping
 6.43 18582#KAA044-001-001: gripping torque with internal gripping
 6.44 18582#KAA045-001-001: manual override
 6.45 18582#KAA046-001-001: stroke
 6.46 18582#KAA047-001-001: stroke per gripper jaw
 6.47 18582#KAA048-001-001: piston diameter
 6.48 18582#KAA049-001-001: type of piston rod
 6.49 18582#KAA050-001-001: type of piston rod end
 6.50 18582#KAA051-001-001: piston rod thread
 6.51 18582#KAA052-001-001: condensate drain
 6.52 18582#KAA053-001-001: logic valve function
 6.53 18582#KAA054-001-001: maximum impact energy
 6.54 18582#KAA055-001-001: maximum stroke reduction per side
 6.55 18582#KAA056-001-001: maximum piston speed
 6.56 18582#KAA057-001-001: maximum condensate volume
 6.57 18582#KAA058-001-001: maximum swivel angle extension per side
 6.58 18582#KAA059-001-001: maximum swivel angle reduction per side
 6.59 18582#KAA060-001-001: maximum temperature of pressure medium
 6.60 18582#KAA061-001-001: maximum ambient temperature
 6.61 18582#KAA062-001-001: maximum output pressure
 6.62 18582#KAA063-001-001: maximum operating pressure
 6.63 18582#KAA064-001-001: maximum pilot pressure
 6.64 18582#KAA065-001-001: maximum X-stroke
 6.65 18582#KAA066-001-001: maximum Y-stroke
 6.66 18582#KAA067-001-001: maximum torque in direction of X-axis
 6.67 18582#KAA068-001-001: maximum torque in direction of Y-axis
 6.68 18582#KAA069-001-001: maximum torque in direction of Z-axis
 6.69 18582#KAA070-001-001: maximum vacuum
 6.70 18582#KAA071-001-001: minimum temperature of pressure medium
 6.71 18582#KAA072-001-001: minimum ambient temperature
 6.72 18582#KAA073-001-001: minimum output pressure
 6.73 18582#KAA074-001-001: minimum operating pressure
 6.74 18582#KAA075-001-001: minimum pilot pressure
 6.75 18582#KAA076-001-001: driver coupling
 6.76 18582#KAA077-001-001: nominal size of pressure gauge
 6.77 18582#KAA078-001-001: nominal size
 6.78 18582#KAA079-001-001: nominal size of laval nozzle
 6.79 18582#KAA080-001-001: pneumatic port
 6.80 18582#KAA081-001-001: pneumatic output port
 6.81 18582#KAA082-001-001: pneumatic input port
 6.82 18582#KAA083-001-001: pneumatic exhaust port
 6.83 18582#KAA084-001-001: pneumatic clamping port
 6.84 18582#KAA085-001-001: pneumatic pilot port
 6.85 18582#KAA086-001-001: position sensing
 6.86 18582#KAA087-001-001: principle of filter contamination indicator
 6.87 18582#KAA088-001-001: shear force
 6.88 18582#KAA089-001-001: grid dimension
 6.89 18582#KAA090-001-001: controller function
 6.90 18582#KAA091-001-001: RoHS conformity
 6.91 18582#KAA092-001-001: IP protection class with connector
 6.92 18582#KAA093-001-001: IP protection class without connector
 6.93 18582#KAA094-001-001: swivel direction
 6.94 18582#KAA095-001-001: swivel angle
 6.95 18582#KAA096-001-001: clamping area
 6.96 18582#KAA097-001-001: shut-off valve function
 6.97 18582#KAA098-001-001: control characteristics
 6.98 18582#KAA099-001-001: type of control
 6.99 18582#KAA100-001-001: flow control valve function
 6.100 18582#KAA101-001-001: theoretical cylinder force, advancing
 6.101 18582#KAA102-001-001: theoretical cylinder force, retracting
 6.102 18582#KAA103-001-001: shifting time

- 6.103 18582#KAA104-001-001: shifting-on time of dominant side
- 6.104 18582#KAA105-001-001: valve return
- 6.105 18582#KAA106-001-001: torsional tolerance
- 6.106 18582#KAA107-001-001: volumetric flow rate due to secondary venting
- 6.107 18582#KAA108-001-001: volumetric flow rate through vacuum filter
- 6.108 18582#KAA109-001-001: volumetric flow rate with respect to atmosphere
- 6.109 18582#KAA110-001-001: directional control valve function
- 6.110 18582#KAA111-001-001: active direction of gripping force backup
- 6.111 18582#KAA112-001-001: effective torque
- 6.112 18582#KAA113-001-001: limit of the axial force
- 6.113 18582#KAA114-001-001: permissible lateral force
- 6.114 18582#KAA115-001-001: certification
- 6.115 18582#KAA116-001-001: ISO standard conformity of cylinder
- 6.116 18582#KAA117-001-001: accessory type

7 Application classes

- 7.1 18582#KAA801-001-001: pneumatics
- 7.2 18582#KAA802-001-001: actuators
- 7.3 18582#KAA803-001-001: valves and valve manifolds
- 7.4 18582#KAA804-001-001: compressed air
- 7.5 18582#KAA805-001-001: vacuum technology

Annex A (informative) Hierarchical structure of the application classes

Page count: 184