

DIN EN ISO 28139:2021-11 (E)

Equipment for crop protection - Knapsack combustion engine-driven airblast sprayers - Safety and environmental requirements and test methods (ISO 28139:2019)

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| Introduction | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 8 |
| 4 | Safety requirements and/or protective measures | 9 |
| 4.1 | General | 9 |
| 4.2 | Stability when in operation | 9 |
| 4.3 | Exhaust system | 9 |
| 4.4 | Air tube and chemical hoses | 9 |
| 4.5 | Controls | 10 |
| 4.5.1 | General | 10 |
| 4.5.2 | Handle | 10 |
| 4.5.3 | Throttle trigger | 11 |
| 4.5.4 | Engine stopping device | 11 |
| 4.5.5 | Starting device | 11 |
| 4.5.6 | Liquid line shut-off valve | 11 |
| 4.6 | Machine support | 11 |
| 4.6.1 | Harness | 12 |
| 4.7 | Power-driven components | 12 |
| 4.8 | Fuel tank | 12 |
| 4.9 | Protection against contact with hot parts | 12 |
| 4.10 | Electrical requirements | 14 |
| 4.10.1 | General | 14 |
| 4.10.2 | Ignition circuit | 14 |
| 4.11 | Vibration | 14 |
| 4.11.1 | Reduction by design at source and by protective measures | 14 |
| 4.11.2 | Vibration measurement | 14 |
| 4.12 | Noise | 14 |
| 4.12.1 | Reduction by design at source and by protective measures | 14 |
| 4.12.2 | Noise measurement | 15 |
| 4.13 | Electromagnetic immunity | 15 |
| 4.13.1 | Requirements | 15 |
| 4.13.2 | Verification | 15 |
| 5 | Environmental requirements | 15 |
| 5.1 | General | 15 |
| 5.2 | Absorbency of carrying straps | 15 |
| 5.3 | Spray tank | 15 |
| 5.4 | Strainers and filters | 16 |
| 5.5 | Droplet size | 17 |
| 5.6 | Air hoses and chemical hoses | 17 |

| | | |
|--|---|----|
| 5.7 | Fan | 17 |
| 5.8 | Mass of total residual liquid | 17 |
| 5.9 | Stability | 17 |
| 5.10 | Spray liquid flow rate | 17 |
| 5.11 | Test report | 18 |
| 6 | Tests | 18 |
| 6.1 | Test liquids and equipment | 18 |
| 6.2 | Test conditions | 19 |
| 6.2.1 | General | 19 |
| 6.2.2 | Engine speed | 19 |
| 6.3 | Spray liquid output | 19 |
| 6.4 | Mass of total residual liquid | 19 |
| 6.5 | Stability | 20 |
| 6.6 | gauge scale and total tank volume | 20 |
| 6.7 | Filling rate | 20 |
| 6.8 | Air velocity | 21 |
| 7 | Information for use | 22 |
| 7.1 | Instruction handbook | 22 |
| 7.1.1 | General | 22 |
| 7.1.2 | Technical data | 24 |
| 7.2 | Marking | 25 |
| 7.3 | Warnings | 25 |
| Annex A (informative) List of significant hazards | | 26 |
| Annex B (normative) Sampling grid position for air velocity determination | | 31 |
| Annex C (normative) Stability test | | 32 |
| Annex D (informative) Example of a knapsack combustion engine-driven airblast sprayer | | 33 |
| Annex E (informative) Safety signs | | 34 |
| Annex F (informative) Position of sprayer and Petri dishes for potential ground deposit determination | | 35 |
| Annex G (informative) Sprayer locking device | | 36 |
| Annex H (informative) Device for detecting potential vertical deposits | | 37 |
| Annex I (informative) Potential ground deposit, potential vertical deposit and droplet size test | | 38 |
| Annex J (informative) Minimum content of test report | | 41 |
| Bibliography | | 45 |