

ISO/TS 6336-4:2019 (E)

Calculation of load capacity of spur and helical gears — Part 4: Calculation of tooth flank fracture load capacity

Contents

| | |
|-------------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms, definitions, symbols and abbreviated terms |
| 3.1 | Terms and definitions |
| 3.2 | Symbols and abbreviated terms |
| 3.3 | Definition of local contact point, CP, and material depth, y |
| 4 | Definition of tooth flank fracture |
| 5 | Basic formulae |
| 5.1 | General |
| 5.2 | Maximum material exposure, AFF,max |
| 5.3 | Local material exposure, $AFF,CP(y)$ |
| 6 | Local occurring equivalent stress, $\tau_{eff,CP}(y)$ |
| 6.1 | General |
| 6.2 | Local equivalent stress without consideration of residual stresses, $\tau_{eff,L,CP}(y)$ |
| 6.2.1 | General |
| 6.2.2 | Local normal radius of relative curvature, $p_{red,CP}$ |
| 6.2.3 | Reduced modulus of elasticity, E_r |
| 6.2.4 | Local Hertzian contact stress, $p_{dyn,CP}$ |
| 6.2.4.1 | Method A |
| 6.2.4.2 | Method B |
| 6.2.4.2.1 | General |
| 6.2.4.2.2 | Local nominal Hertzian contact stress, p_H,CP,B |
| 6.2.4.2.3 | Definition of contact point, CP, on the path of contact |
| 6.2.4.2.4 | Local load sharing factor, XCP |
| 6.2.4.2.4.1 | General |
| 6.2.4.2.4.2 | Spur gears with unmodified profiles |
| 6.2.4.2.4.3 | Spur gears with profile modification |
| 6.2.4.2.4.4 | Local buttressing factor, $X_{but,CP}$ |
| 6.2.4.2.4.5 | Helical gears with $\epsilon\beta \leq 0,8$ and unmodified profiles |
| 6.2.4.2.4.6 | Helical gears with $\epsilon\beta \leq 0,8$ and profile modification |
| 6.2.4.2.4.7 | Helical gears with $\epsilon\beta \geq 1,2$ and unmodified profiles |
| 6.2.4.2.4.8 | Helical gears with $\epsilon\beta \geq 1,2$ and profile modification |
| 6.2.4.2.4.9 | Helical gears with $0,8 < \epsilon\beta < 1,2$ |
| 6.3 | Quasi-stationary residual stress, $\tau_{eff,RS}(y)$ |
| 6.3.1 | General |
| 6.3.2 | Method A |
| 6.3.3 | Method B |
| 6.4 | Influence of the residual stresses on the local equivalent stress, $\Delta\tau_{eff,L,RS,CP}(y)$ |
| 7 | Local material strength, $\tau_{per,CP}(y)$ |
| 7.1 | General |
| 7.2 | Hardness conversion factor $K_{T,per}$ |
| 7.3 | Material factor $K_{material}$ |
| 7.4 | Hardness depth profile, $HV(y)$ |

- 7.4.1 General
- 7.4.2 Method A
- 7.4.3 Method B
- 7.4.4 Method C1
- 7.4.5 Method C2

Annex A (informative) Calculation of local equivalent stress without consideration of residual stresses, $\tau_{eff,L,CP}(y)$

Page count: 28