

ISO 11783-2:2019 (E)

Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 2: Physical layer

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Abbreviated terms |
| 5 | General requirements |
| 5.1 | Network physical layer |
| 5.2 | Physical media |
| 5.3 | Differential voltage |
| 5.4 | Bus |
| 5.4.1 | Levels |
| 5.4.1.1 | General |
| 5.4.1.2 | During arbitration |
| 5.4.2 | Voltage range |
| 5.4.3 | Bus termination |
| 5.4.3.1 | Twisted quad bus segment |
| 5.4.3.2 | Twisted pair physical layer bus segment |
| 5.5 | Resistance and capacitance |
| 5.5.1 | Internal resistance (R_{in}), capacitance (C_{in}) |
| 5.5.2 | Differential internal resistance (R_{diff}), capacitance (C_{diff}) |
| 5.5.3 | Weak termination for stubs |
| 5.6 | Bit time |
| 5.7 | AC parameters |
| 6 | Bus segment specifications |
| 6.1 | Twisted quad bus segment |
| 6.2 | TPPL bus segment |
| 7 | Electrical specifications |
| 7.1 | Electrical data |
| 7.1.1 | General |
| 7.1.2 | Absolute maximum ratings |
| 7.1.3 | DC parameters |
| 7.1.3.1 | Power supply operating ranges |
| 7.1.3.2 | Power supply minimum current |
| 7.1.3.3 | Requirements for DC voltage supplied by tractor through the IBBC |
| 7.1.3.4 | Requirements for DC voltage drop on implements |
| 7.1.3.5 | Bus-disconnected ECU |
| 7.1.3.6 | Bus-connected ECU |
| 7.1.4 | Bus voltages (operational) |
| 7.1.5 | Electrostatic discharge (ESD) |
| 7.2 | Physical media parameters |
| 7.2.1 | Unshielded twisted quad cable |
| 7.2.2 | Unshielded twisted pair |
| 7.3 | Topology of twisted quad physical layers |
| 7.3.1 | ECU connection to TBC_PWR and TBC_RTN |

| | |
|----------------|---|
| 7.3.2 | Power for TBC_PWR and TBC_RTN |
| 7.4 | Topology of twisted pair physical layer |
| 7.4.1 | General |
| 7.4.2 | Simple stub |
| 7.4.3 | Compound stub |
| 7.4.4 | Multiple splice |
| 7.5 | TBC parameters |
| 7.6 | Connectors |
| 7.6.1 | General |
| 7.6.1.1 | Electrical performance |
| 7.6.1.2 | Mechanical characteristics |
| 7.6.2 | Bus extension connector |
| 7.6.2.1 | General |
| 7.6.2.2 | Dimensions |
| 7.6.2.3 | Pin allocations |
| 7.6.3 | Implement bus breakaway connector |
| 7.6.3.1 | General |
| 7.6.3.2 | Terminating bias circuit for TQPL IBBC |
| 7.6.3.3 | Terminating circuit for twisted pair physical layer IBBC |
| 7.6.3.4 | Dimensions |
| 7.6.3.5 | Pin allocations |
| 7.6.3.6 | Ground isolation |
| 7.6.3.7 | Backward compatibility |
| 7.6.4 | In-cab connector |
| 7.6.4.1 | General |
| 7.6.4.2 | In-cab connector receptacle dimensions |
| 7.6.4.3 | In-cab connector pin allocations |
| 7.6.4.4 | In-cab connector plug dimensions |
| 7.6.4.5 | In-cab connector cable connections for TQPL |
| 7.6.4.6 | In-cab connector cable connections for TPPL |
| 7.6.5 | Diagnostic connector |
| 7.6.5.1 | General |
| 7.6.5.2 | Receptacle dimensions |
| 7.6.5.3 | Locking plug dimensions |
| 7.6.5.4 | Non-locking plug dimensions |
| 7.6.5.5 | Pin allocations |
| 7.6.5.6 | Diagnostic connector dimensions |
| 8 | Conformance tests |
| 8.1 | General requirements |
| 8.2 | Internal resistance |
| 8.3 | Internal differential resistance |
| 8.4 | ECU recessive input threshold |
| 8.5 | ECU dominant input threshold |
| 8.6 | ECU dominant output |
| 8.7 | ECU internal delay time |
| 9 | Bus failure and fault confinement |
| 9.1 | General |
| 9.2 | Loss of network connection |
| 9.3 | Node power or ground loss |
| 9.4 | Reaction to power-supply voltage disturbances |
| 9.5 | Network disruption during connection, disconnection or power-up |
| 9.6 | Open and short failures |
| Annex A | (informative) Protocol controller timing and naming |
| A.1 | Bit subdivision |
| A.2 | Internal delay time |
| A.3 | Synchronization |
| A.4 | Synchronization jump width (SJW) |
| A.5 | CAN bit timing requirements |
| Annex B | (informative) Examples of physical layer circuits |
| B.1 | General |

| | |
|----------------|--|
| B.2 | Network interconnection |
| B.3 | Terminating bias circuit |
| B.4 | Automatic TBC at bus breakaway connector |
| B.5 | Optional TBC unit |
| B.6 | Circuits for power control |
| Annex C | (informative) Optional ECU stub connector |
| C.1 | General |

Page count: 65