ISO 8100-30:2019-10 (E)

Lifts for the transport of persons and goods - Part 30: Class I, II, III and VI lifts installation

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1
3.1 General 1
3.2 Terms related to lift classes 2
3.3 Terms related to dimensions 2
3.4 Terms related to other characteristics 6

4 Lift characteristics 6
4.1 Renard series 6
4.2 Rated loads 7
4.3 Rated speeds 7
4.4 Selection of class of lift 7

5 Dimensions 7
5.1 Inner dimensions of cars 7
5.1.1 Accessibility 7
5.1.2 Class I lifts 7
5.1.3 Class II lifts 8
5.1.4 Class III lifts 8
5.1.5 Class VI lifts 8
5.2 Inner dimensions of well 8
5.2.1 Plan dimensions 8
5.2.2 Individual lifts 12
5.2.3 Multiple lifts situated side by side 12
5.2.4 Distance between landings 12
5.2.5 Class III lifts 12
5.3 Dimensions of landings 12
5.3.1 General 12
5.3.2 Class I lifts particularly intended for residential buildings 13
5.3.3 Class I (other than those particularly intended for residential buildings), II, III and VI lifts .13
5.4 Dimensions of machine room for electric lifts 13
5.4.1 General 13
5.4.2 Individual lifts 13
5.4.3 Multiple lifts 13
5.5 Dimensions of machine room for hydraulic lifts 15
5.5.1 General 15
5.5.2 Individual lifts 15
5.5.3 Duplex group lifts 15
5.6 Arrangement of machine room (where applicable) 15
5.6.1 Individual or common arrangement 15
5.6.2 Arrangement for individual lifts and multiple lifts side by side with common machine room 17
5.6.3 Arrangement for lifts face to face with a common machine room (for electric lifts only) 18

Bibliography 30