

# ISO 6336-1:2019-11 (E)

## Calculation of load capacity of spur and helical gears - Part 1: Basic principles, introduction and general influence factors

---

<b>Contents</b>		<b>Page</b>
Foreword .....		vi
Introduction .....		vii
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>2</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviated terms .....</b>	<b>2</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>3.2</b>	<b>Symbols and abbreviated terms .....</b>	<b>2</b>
<b>4</b>	<b>Basic principles .....</b>	<b>11</b>
<b>4.1</b>	<b>Application .....</b>	<b>11</b>
<b>4.1.1</b>	<b>Surface durability (pitting) .....</b>	<b>11</b>
<b>4.1.2</b>	<b>Tooth bending strength .....</b>	<b>11</b>
<b>4.1.3</b>	<b>Tooth flank fracture .....</b>	<b>12</b>
<b>4.1.4</b>	<b>Strength and quality of materials .....</b>	<b>12</b>
<b>4.1.5</b>	<b>Service life under variable load .....</b>	<b>12</b>
<b>4.1.6</b>	<b>Scuffing .....</b>	<b>12</b>
<b>4.1.7</b>	<b>Wear .....</b>	<b>12</b>
<b>4.1.8</b>	<b>Micropitting .....</b>	<b>12</b>
<b>4.1.9</b>	<b>Plastic-yielding .....</b>	<b>12</b>
<b>4.1.10</b>	<b>Specific applications .....</b>	<b>12</b>
<b>4.1.11</b>	<b>Safety factors .....</b>	<b>13</b>
<b>4.1.12</b>	<b>Testing .....</b>	<b>15</b>
<b>4.1.13</b>	<b>Manufacturing tolerances .....</b>	<b>15</b>
<b>4.1.14</b>	<b>Implied accuracy .....</b>	<b>15</b>
<b>4.1.15</b>	<b>Other considerations .....</b>	<b>15</b>
<b>4.1.16</b>	<b>Influence factors .....</b>	<b>16</b>
<b>4.1.17</b>	<b>Numerical formulae .....</b>	<b>18</b>
<b>4.1.18</b>	<b>Succession of factors in the course of calculation .....</b>	<b>18</b>
<b>4.1.19</b>	<b>Determination of allowable values of gear deviations .....</b>	<b>18</b>
<b>4.2</b>	<b>Tangential load, torque and power .....</b>	<b>18</b>
<b>4.2.1</b>	<b>General .....</b>	<b>18</b>
<b>4.2.2</b>	<b>Nominal tangential load, nominal torque and nominal power .....</b>	<b>19</b>
<b>4.2.3</b>	<b>Equivalent tangential load, equivalent torque and equivalent power .....</b>	<b>19</b>
<b>4.2.4</b>	<b>Maximum tangential load, maximum torque and maximal power .....</b>	<b>19</b>
<b>5</b>	<b>Application factor, KA .....</b>	<b>19</b>
<b>5.1</b>	<b>General .....</b>	<b>19</b>
<b>5.2</b>	<b>Method A -- Factor KA-A .....</b>	<b>20</b>
<b>5.2.1</b>	<b>Factor KA-A .....</b>	<b>20</b>
<b>5.2.4</b>	<b>Factor KFFA-A for tooth flank fracture along ISO/TS 6336-4 .....</b>	<b>20</b>
<b>5.2.5</b>	<b>Factor KA-A for scuffing along ISO/TS 6336-20/ISO/TS 6336-21 .....</b>	<b>21</b>
<b>5.2.6</b>	<b>Factor KA-A for micropitting along ISO/TS 6336-22 .....</b>	<b>21</b>
<b>5.3</b>	<b>Method B -- Factor KA-B .....</b>	<b>21</b>
<b>5.3.1</b>	<b>General .....</b>	<b>21</b>
<b>5.3.2</b>	<b>Guide values for application factor, KA-B .....</b>	<b>21</b>
<b>6</b>	<b>Internal dynamic factor, Kv .....</b>	<b>24</b>

6.1	General .....	24
6.2	Parameters affecting internal dynamic load and calculations .....	24
6.2.1	Design .....	24
6.2.2	Manufacturing .....	24
6.2.3	Transmission perturbation .....	25
6.2.4	Dynamic response .....	25
6.2.5	Resonances .....	25
6.2.6	Application of internal dynamic factor for low loaded gears .....	26
6.3	Principles and assumptions .....	26
6.4	Methods for determination of dynamic factor .....	27
6.4.1	Method A -- Factor Kv-A .....	27
6.4.2	Method B -- Factor Kv-B .....	27
6.4.3	Method C -- Factor Kv-C .....	27
6.5	Determination of dynamic factor using Method B: Kv-B .....	28
6.5.1	General .....	28
6.5.2	Running speed ranges .....	28
6.5.3	Determination of resonance running speed (main resonance) of a gear pair .....	29
6.5.4	Dynamic factor in subcritical range ( $N < N_{NS}$ ) .....	31
6.5.5	Dynamic factor in main resonance range ( $N_{NS} < N < 1,15$ ) .....	34
6.5.6	Dynamic factor in supercritical range ( $N > 1,5$ ) .....	34
6.5.7	Dynamic factor in intermediate range ( $1,15 < N < 1,5$ ) .....	34
6.5.8	Resonance speed determination for specific gear designs .....	35
6.5.9	Calculation of reduced mass of gear pair with external teeth .....	37
6.6	Determination of dynamic factor using Method C: Kv-C .....	38
6.6.1	General .....	38
6.6.2	Graphical values of dynamic factor using Method C .....	39
6.6.3	Determination by calculation of dynamic factor using Method C .....	42
7	Face load factors, KH and KF .....	43
7.1	Gear tooth load distribution .....	43
7.2	General principles for determination of face load factors, KH and KF .....	43
7.2.1	General .....	43
7.2.2	Face load factor for contact stress, KH .....	44
7.2.3	Face load factor for tooth root stress, KF .....	44
7.3	Methods for determination of face load factor -- Principles, assumptions .....	44
7.3.1	General .....	44
7.3.2	Method A -- Factors KH-A and KF-A .....	44
7.3.3	Method B -- Factors KH-B and KF-B .....	45
7.3.4	Method C -- Factors KH-C and KF-C .....	45
7.4	Determination of face load factor using Method B: KH-B .....	45
7.4.1	Number of calculation points .....	45
7.4.2	Definition of KH .....	45
7.4.3	Stiffness and elastic deformations .....	45
7.4.4	Static displacements .....	49
7.4.5	Assumptions .....	49
7.4.6	Computer program output .....	49
7.5	Determination of face load factor using Method C: KH-C .....	49
7.5.1	General .....	49
7.5.2	Effective equivalent misalignment, $F_y$ .....	51
7.5.3	Running-in allowance, $y$ , and running-in factor, .....	51
7.5.4	Mesh misalignment, $f_{ma}$ .....	61
7.5.5	Component of mesh misalignment caused by case deformation, $f_{ca}$ .....	63
7.5.6	Component of mesh misalignment caused by shaft displacement, $f_{be}$ .....	63
7.6	Determination of face load factor for tooth root stress using Method B or C: KF .....	64
8	Transverse load factors KH and KF .....	65
8.1	Transverse load distribution .....	65
8.2	Determination methods for transverse load factors -- Principles and assumptions .....	65
8.2.1	General .....	65
8.2.2	Method A -- Factors KH-A and KF-A .....	65
8.2.3	Method B -- Factors KH-B and KF-B .....	66

8.3	Determination of transverse load factors using Method B -- KH-B and KF-B .....	66
8.3.1	General .....	66
8.3.2	Determination of transverse load factor by calculation .....	66
8.3.3	Transverse load factors from graphs .....	67
8.3.4	Limiting conditions for KH .....	67
8.3.5	Limiting conditions for KF .....	67
8.3.6	Running-in allowance, $y$ .....	68
9	Tooth stiffness parameters, $c$ and $c_c$ .....	71
9.1	Stiffness influences .....	71
9.2	Determination methods for tooth stiffness parameters -- Principles and assumptions .....	71
9.2.1	General .....	71
9.2.2	Method A -- Tooth stiffness parameters $c_A$ and $c_{c-A}$ .....	72
9.2.3	Method B -- Tooth stiffness parameters $c_B$ and $c_{c-B}$ .....	72
9.3	Determination of tooth stiffness parameters, $c$ and $c_c$ , according to Method B .....	72
9.3.1	General .....	72
9.3.2	Single stiffness, $c$ .....	73
9.3.3	Mesh stiffness, $c_c$ .....	77
10	Parameter of Hertzian contact .....	77
10.1	Local radius of relative curvature .....	77
10.2	Reduced modulus of elasticity, $E_r$ .....	78
10.3	Local Hertzian contact stress, $p_{dyn,CP}$ .....	78
10.3.1	Method A .....	78
10.3.2	Method B .....	79
10.4	Half of the Hertzian contact width, $b_H$ .....	80
10.5	Load distribution along the path of contact .....	80
10.5.1	Definition of contact points, CP, on the path of contact .....	80
10.5.2	Load sharing factor, XCP .....	82
10.6	Sum of tangential velocity, $v_{,CP}$ .....	90
11	Lubricant parameters at given temperature .....	91
11.1	General .....	91
11.2	Kinematic viscosity at a given temperature, $\nu$ .....	91
11.3	Density of the lubricant at a given temperature, $\rho$ .....	92
Annex A (normative) Additional methods for determination of $f_{sh}$ and $f_{ma}$ .....		93
Annex B (informative) Guide values for crowning and end relief of teeth of cylindrical gears .....		96
Annex C (informative) Guide values for KH-C for crowned teeth of cylindrical gears .....		99
Annex D (informative) Derivations and explanatory notes .....		102
Annex E (informative) Analytical determination of load distribution .....		106
Annex F (informative) General symbols used for calculation of load capacity of spur and helical gears .....		128
Bibliography .....		133