

# ISO 6336-2:2019-11 (E)

## Calculation of load capacity of spur and helical gears - Part 2: Calculation of surface durability (pitting)

---

Contents		Page
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms, definitions, symbols and abbreviated terms .....	2
3.1	Terms and definitions .....	2
3.2	Symbols and abbreviated terms .....	2
4	Pitting damage and safety factors .....	6
5	Basic formulae .....	7
5.1	General .....	7
5.2	Safety factor for surface durability (against pitting), SH .....	8
5.3	Contact stress, H .....	8
5.4	Permissible contact stress, HP .....	9
5.4.1	General .....	9
5.4.2	Determination of permissible contact stress, HP -- Principles, assumptions and application .....	10
5.4.3	Permissible contact stress, HP: Method B .....	10
5.4.4	Permissible contact stress for limited and long life: Method B .....	11
6	Zone factor, ZH, and contact factors, ZB and ZD .....	13
6.1	General .....	13
6.2	Zone factor, ZH .....	14
6.2.1	General .....	14
6.2.2	Graphical values .....	14
6.2.3	Determination by calculation .....	14
6.3	Contact factors, ZB and ZD, for $\alpha < 20^\circ$ .....	14
6.4	Contact factors, ZB and ZD, for $\alpha > 20^\circ$ .....	17
7	Elasticity factor, ZE .....	17
8	Contact ratio factor, Z .....	18
8.1	General .....	18
8.2	Determination of contact ratio factor, Z .....	18
8.2.1	Graphical values .....	18
8.2.2	Determination by calculation .....	19
8.3	Calculation of transverse contact ratio, $\alpha_t$ , and overlap ratio, $\epsilon$ , .....	20
8.3.1	Transverse contact ratio, $\alpha_t$ .....	20
8.3.2	Overlap ratio, $\epsilon$ .....	20
9	Helix angle factor, Z <sub>β</sub> .....	21
10	Strength for contact stress .....	21
10.1	General .....	21
10.2	Allowable stress numbers (contact), H <sub>lim</sub> : Method B .....	21
10.3	Allowable stress number values: Method BR .....	22

11	Life factor, ZNT(forflanks) .....	22
11.1	General .....	22
11.2	Life factor, ZNT: Method A .....	22
11.3	Life factor, ZNT: Method B .....	22
12	Influenceoflubricantfilm,factorsZL, Zv and ZR .....	24
12.1	General .....	24
12.2	Influence of lubricant film: Method A .....	24
12.3	Influence of lubricant film, factors ZL, Zv and ZR: Method B .....	24
12.3.1	General .....	24
12.3.2	Factors ZL, Zv and ZR for reference stress .....	25
12.3.3	Factors ZL, Zv and ZR for static stress .....	30
13	Workhardeningfactor,ZW .....	30
13.1	General .....	30
13.2	Work hardening factor, ZW: Method A .....	30
13.3	Work hardening factor, ZW: Method B .....	31
13.3.1	Surface-hardened steel pinion with through-hardened steel gear .....	31
13.3.2	Through-hardened steel pinion with through-hardened steel gear .....	33
13.3.3	Surface-hardened steel pinion with ductile iron gear .....	34
14	Size factor, ZX .....	36
	Bibliography .....	37