ISO 6336-3:2019-11 (E)

Calculation of load capacity of spur and helical gears - Part 3: Calculation of tooth bending strength

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms,definitions,symbolsandabbreviatedterms 2
3.1 Terms and definitions 2
3.2 Symbols and abbreviated terms 2

4 Tooth breakage and safety factors 7

5 Basic formulae 7
5.1 General 7
5.2 Safety factor for bending strength (safety against tooth breakage), SF 8
5.3 Tooth root stress, F 8
5.3.1 General 8
5.3.2 Method A 8
5.3.3 Method B 8
5.4 Permissible bending stress, FP 10
5.4.1 General 10
5.4.2 Methods for determination of permissible bending stress, FP -- Principles, assumptions and application 10
5.4.3 Permissible bending stress, FP: Method B 11
5.4.4 Permissible bending stress, FP, for limited and long life: Method B 12

6 Form factor, YF 14
6.1 General 14
6.2 Calculation of the form factor, YF: Method B 15
6.2.1 General 15
6.2.2 Parameters of virtual gears 17
6.2.3 Tooth root normal chord, sFn, radius of root fillet, F, bending moment arm, hFe for external gears generated with a hob 18
6.2.4 Tooth root normal chord, sFn , radius of root fillet, F , bending moment arm, hFe for external gears generated with a shaper cutter2) 19
6.2.5 Tooth root normal chord, sFn, radius of root fillet, F, bending moment arm, hFe for internal gears generated with a shaper cutter2) 24

7 Stress correction factor, YS 24
7.1 Basic uses 24
7.2 Stress correction factor, YS: Method B 24
7.3 Stress correction factor for gears with notches in fillets 25
7.4 Stress correction factor, YST, relevant to the dimensions of the standard reference test gears 25

8 Helix angle factor, Y 26
8.1 General 26
8.2 Graphical value 26
8.3 Determination by calculation 26

9 Rim thickness factor, YB 27
9.1 General 27
9.2 Graphical values 27
9.3 Determination by calculation 27
9.3.1 External gears 27
9.3.2 Internal gears 28

10 Deep tooth factor, YDT 28
10.1 General 28

10.2 Graphical values 28
10.3 Determination by calculation 29

11 Reference stress for bending 29
11.1 General 29
11.2 Reference stress for Method A 29
11.3 Reference stress, with values F lim and FE for Method B 29

12 Life factor, YNT 29
12.1 General 29
12.2 Life factor, YNT: Method A 30
12.3 Life factor, YNT: Method B 30
12.3.1 General 30
12.3.2 Graphical values 30
12.3.3 Determination by calculation 31

13 Notch sensitivity factor, YT, and relative notch sensitivity factor, Y rel T 32
13.1 Basic uses 32
13.2 Determination of the notch sensitivity factors 32
13.2.1 General 32
13.2.2 Method A 32
13.2.3 Method B 32
13.3 Relative notch sensitivity factor, Y rel T: Method B 32
13.3.1 Graphical values 32
13.3.2 Determination by calculation 33

14 Surface factors, YR, YRT, and relative surface factor, YR rel T 38
14.1 Influence of surface condition 38
14.2 Determination of surface factors and relative surface factors 39
14.2.1 General 39
14.2.2 Method A 39
14.2.3 Method B 39
14.3 Relative surface factor, YR rel T: Method B 39
14.3.1 Graphical values 39
14.3.2 Determination by calculation 40

15 Size factor, YX 41
15.1 General 41
15.2 Size factor, YX: Method A 41
15.3 Size factor, YX: Method B 41
15.3.1 General 41
15.3.2 Graphical values for reference stress and static stress 41
15.3.3 Determination by calculation 42

Annex A (normative) Permissible bending stress, FP,obtainedfromnotched,flatorplain polished test pieces 44

Annex B (informative)Guidevaluesformeanstressinfluencefactor,YM 52

Annex C (informative) Derivations of determinant normal tooth load of spur gears 54

Bibliography 55