

ISO 10303-503:2000-03 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 503: Application interpreted construct: Geometrically bounded 2D wireframe

Contents		Page
1	Scope	1
2	Normative references	1
3	Definitions and abbreviations	2
3.3	Abbreviations	3
4	EXPRESS short listing	3
4.1	Introduction	4
4.2	Fundamental concepts and assumptions	4
4.3	aic_geometrically_bounded_2d_wireframe entity definition: geometrically_bounded_2d_wireframe_representation	4
4.4	aic_geometrically_bounded_2d_wireframe function definition: valid_basis_curve_in_2d_wireframe	6
Annex A (normative) Short names of entities		8
Annex B (normative) Information object registration		9
B.1	Document identification	9
B.2	Schema identification	9
Annex C (informative) EXPRESS-G diagrams		10
Annex D (informative) Computer interpretable listings		16
Index		17
Figures Figure C.1 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 1 of 5		11
Figure C.2 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 2 of 5		12
Figure C.3 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 3 of 5		13
Figure C.4 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 4 of 5		14
Figure C.5 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 5 of 5		15
Tables Table A.1 - Short names of entities		8