# ISO 10303-503:2000-03 (E)

## Industrial automation systems and integration - Product data representation and exch ange - Part 503: Application interpreted construct: Geometrically bounded 2D wireframe

## Contents

Page


1 Scope ....1

2 Normative references ....1

3 Definitions and abbreviations ....2
3.3 Abbreviations ....3

4 EXPRESS short listing ....3
4.1 Introduction ....4
4.2 Fundamental concepts and assumptions ....4
4.3 aic_geometrically_bounded_2d_wireframe entity definition: geometrically_bounded_2d_wireframe_representation ....4
4.4 aic_geometrically_bounded_2d_wireframe function definition: valid_basis_curve_in_2d_wireframe ....6

Annex A (normative) Short names of entities ....8

Annex B (normative) Information object registration ....9

B.1 Document identification ....9
B.2 Schema identification ....9

Annex C (informative) EXPRESS-G diagrams ....10

Annex D (informative) Computer interpretable listings ....16

Index ....17

Figures Figure C.1 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 1 of 5 ....11

Figure C.2 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 2 of 5 ....12

Figure C.3 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 3 of 5 ....13

Figure C.4 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 4 of 5 ....14

Figure C.5 - aic_geometrically_bounded_2d_wireframe - EXPRESS-G diagram 5 of 5 ....15

Tables Table A.1 - Short names of entities ....8