

ISO 10303-510:2000-03 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 510: Application interpreted construct: Geometrically bounded wireframe

Contents		Page
1	Scope	1
2	Normative references	1
3	Definitions and abbreviations	2
3.3	Abbreviations	3
4	EXPRESS short listing	3
4.1	Introduction	4
4.2	Fundamental concepts and assumptions	4
4.3	aic_geometrically_bounded_wireframe entity definition: geometrically_bounded_wireframe_shape_representation	5
4.4	aic_geometrically_bounded_wireframe function definitions	7
4.4.1	valid_geometrically_bounded_wf_curve	7
4.4.2	valid_geometrically_bounded_wf_point	8
	Annex A (normative) Short names of entities	10
	Annex B (normative) Information object registration	11
B.1	Document identification	11
B.2	Schema identification	11
	Annex C (informative) EXPRESS-G diagrams	12
	Annex D (informative) Computer interpretable listings	19
	Index	20
	Figures Figure C.1 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 1 of 6	13
	Figure C.2 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 2 of 6	14
	Figure C.3 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 3 of 6	15
	Figure C.4 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 4 of 6	16
	Figure C.5 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 5 of 6	17
	Figure C.6 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 6 of 6	18
	Tables Table A.1 - Short names of entities	10