ISO 10303-510:2000-03 (E)

Industrial automation systems and integration - Product data representat ion and exchange - Part 510: Application interpreted construct: Geometrically bounded wireframe

Contents

Page

1 Scope 1

2 Normative references 1

3 Definitions and abbreviations 2
3.3 Abbreviations 3

4 EXPRESS short listing 3
4.1 Introduction 4
4.2 Fundamental concepts and assumptions 4
4.3 aic_geometrically_bounded_wireframe entity definition: geometrically_bounded_wireframe_shape_representation 5
4.4 aic_geometrically_bounded_wireframe function definitions 7
4.4.1 valid_geometrically_bounded_wf_curve 7
4.4.2 valid_geometrically_bounded_wf_point 8

Annex A (normative) Short names of entities 10

Annex B (normative) Information object registration 11

B.1 Document identification 11
B.2 Schema identification 11

Annex C (informative) EXPRESS-G diagrams 12

Annex D (informative) Computer interpretable listings 19

Index 20

Figures Figure C.1 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 1 of 6 13

Figure C.2 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 2 of 6 14

Figure C.3 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 3 of 6 15

Figure C.4 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 4 of 6 16

Figure C.5 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 5 of 6 17

Figure C.6 - aic_geometrically_bounded_wireframe - EXPRESS-G diagram 6 of 6 18

Tables Table A.1 - Short names of entities 10