

ISO 10303-519:2000-03 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 519: Application interpreted construct: Geometric tolerances

Contents		Page
1	Scope	1
2	Normative references	2
3	Terms, definitions, and abbreviations	3
3.3	Terms defined in ISO 5459	4
3.4	Terms defined in ISO TS 17450	4
3.5	Other definitions	4
3.6	Abbreviations	5
4	EXPRESS short listing	5
4.1	Fundamental concepts and assumptions	6
4.2	AIC geometric tolerances entity definitions	8
4.2.1	angularity tolerance	8
4.2.2	circular runout tolerance	9
4.2.3	coaxiality tolerance	9
4.2.4	common datum	10
4.2.5	concentricity tolerance	11
4.2.6	cylindricity tolerance	11
4.2.7	flatness tolerance	12
4.2.8	line profile tolerance	13
4.2.9	parallelism tolerance	14
4.2.10	perpendicularity tolerance	15
4.2.11	position tolerance	15
4.2.12	roundness tolerance	16
4.2.13	straightness tolerance	17
4.2.14	surface profile tolerance	18
4.2.15	symmetry tolerance	18
4.2.16	total runout tolerance	19
	Annex A normative Short names of entities	20
	Annex B normative Information object registration	21
B.1	Document identification	21
B.2	Schema identification	21
	Annex C informative EXPRESS-G diagrams	22
	Annex D informative Computer interpretable listings	28
	Index	29
	Figures Figure C.1 AIC expanded listing diagram in EXPRESS G: 1 of 5	23
	Figure C.2 AIC expanded listing diagram in EXPRESS G: 2 of 5	24
	Figure C.3 AIC expanded listing diagram in EXPRESS G: 3 of 5	25
	Figure C.4 AIC expanded listing diagram in EXPRESS G: 4 of 5	26
	Figure C.5 AIC expanded listing diagram in EXPRESS G: 5 of 5	27
	Tables Table A.1 Short names of entities	20