ISO 7241-2:2000-03 (E)

Hydraulic fluid power - Quick-action couplings - Part 2: Test methods

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Selection and examination of test samples 2

5 Test apparatus 2

6 Test conditions 2

7 Connect force test 2

8 Disconnect force test 2

9 Leakage test 3
9.1 Low pressure, coupled 3
9.2 Low pressure, uncoupled (valved only) 4
9.3 Maximum operating pressure, coupled 5
9.4 Maximum operating pressure, uncoupled (valved only) 5

10 Extreme temperature test 5
10.1 Maximum operating temperature exposure, coupled 5
10.2 Maximum operating temperature exposure, uncoupled (valved only) 5
10.3 Maximum operating temperature service, coupled 5
10.4 Maximum operating temperature service, uncoupled (valved only) 6
10.5 Minimum operating temperature, coupled 6
10.6 Minimum operating temperature, uncoupled (valved only) 6

11 Pressure impulse test 6
11.1 Test coupling 6
11.2 Coupled test 6
11.3 Uncoupled test (valved only) 7

12 Rotating impulse test 7

13 Endurance test 7

14 Pressure drop test 8

15 Vacuum test 9
15.1 Coupled test 9
15.2 Uncoupled test (valved only) 11

16 Air inclusion test 11

17 Spillage test 11

18 Static pressure test 13
18.1 Coupled 13
18.2 Uncoupled (valved type only) 14

19 Surge flow test -- long duration 14

20 Surge flow test - short duration 14

21 Burst test 16
21.1 Safety precautions 16
21.2 Burst pressure, uncoupled (valved type only) 16
21.3 Burst pressure, coupled 16

22 Data accuracy 16

23 Test report and data presentation 16

24 Summary of information to be supplied 16

25 Test/production similarity 17

Annex A (normative) Test data form 18