

ISO 7241-2:2000-03 (E)

Hydraulic fluid power - Quick-action couplings - Part 2: Test methods

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Selection and examination of test samples	2
5	Test apparatus	2
6	Test conditions	2
7	Connect force test	2
8	Disconnect force test	2
9	Leakage test	3
9.1	Low pressure, coupled	3
9.2	Low pressure, uncoupled (valved only)	4
9.3	Maximum operating pressure, coupled	5
9.4	Maximum operating pressure, uncoupled (valved only)	5
10	Extreme temperature test	5
10.1	Maximum operating temperature exposure, coupled	5
10.2	Maximum operating temperature exposure, uncoupled (valved only)	5
10.3	Maximum operating temperature service, coupled	5
10.4	Maximum operating temperature service, uncoupled (valved only)	6
10.5	Minimum operating temperature, coupled	6
10.6	Minimum operating temperature, uncoupled (valved only)	6
11	Pressure impulse test	6
11.1	Test coupling	6
11.2	Coupled test	6
11.3	Uncoupled test (valved only)	7
12	Rotating impulse test	7
13	Endurance test	7
14	Pressure drop test	8
15	Vacuum test	9
15.1	Coupled test	9
15.2	Uncoupled test (valved only)	11
16	Air inclusion test	11
17	Spillage test	11

18	Static pressure test	13
18.1	Coupled	13
18.2	Uncoupled (valved type only)	14
19	Surge flow test -- long duration	14
20	Surge flow test - short duration	14
21	Burst test	16
21.1	Safety precautions	16
21.2	Burst pressure, uncoupled (valved type only)	16
21.3	Burst pressure, coupled	16
22	Data accuracy	16
23	Test report and data presentation	16
24	Summary of information to be supplied	16
25	Test/production similarity	17
	Annex A (normative) Test data form	18