DIN EN 16480:2022-07 (E)

Pumps - Rotodynamic pumps - Minimum required efficiency of water pumps and determination of Minimum Efficiency Index (MEI)

Contents

Page

European foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5
3.1 List of quantities with definitions 5
3.2 General definitions 7

4 Symbols and abbreviations 8

5 Minimum Required Efficiencies and Minimum Efficiency Index 10
5.1 The concept of "house of efficiency" 10
5.2 Mathematical representation of minimum required efficiency 12
5.3 Minimum efficiency at part load and overload 13
5.4 Minimum Efficiency Index 13

6 Determination of the Efficiency of a Test Pump 16
6.1 General 16
6.2 Test Procedures 16
6.3 Test conditions 17
6.4 Measurement uncertainties 18
6.4.1 Relevance 18
6.4.2 Fluctuations 18
6.4.3 Statistical evaluation of overall measurement uncertainty 18
6.5 Evaluation of test data 20
6.5.1 Conversion of the test results to the nominal speed of rotation or to the nominal electric frequency 20
6.5.2 Performance curves 21
6.5.3 Determination of the values relevant for the qualification of MEI 22
6.5.4 Procedures for testing and/or evaluation of special pump types 23

7 Proving the Minimum Efficiency Index of a pump size 24
7.1 General remarks 24
7.2 Determination of the Minimum Efficiency Index of a pump size 24

Annex A (normative) Pump types in scope 27

Annex B (informative) General remarks on the efficiency of rotodynamic pumps 29

Annex C (informative) Mean Values of Minimum Efficiency Index for a Pump Size 31

C.1 General 31
C.2 Confidence interval on the mean value 32
C.3 Outlier test 34
C.4 Numerical example 35

Annex ZA (informative) Relationship between this European Standard and the Ecodesign requirements of Commission Regulation (EU) No 547/2012 [OJEU L 165/28 of 26 June 2012] aimed to be covered 37

Bibliography 38