# ISO/TS 10300-20:2021 (E)

## Calculation of load capacity of bevel gears — Part 20: Calculation of scuffing load capacity — Flash temperature method

# Contents


Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols

5 Virtual cylindrical gear

5.1 General
5.2 Local geometry parameters
5.2.1 Transverse path of contact
5.2.2 Length of contact lines
5.2.3 Local equivalent radius of curvature, ρrel,Y
5.2.4 Local load sharing factor, XLS,Y

6 Stresses and velocities

6.1 Local modified contact stress, σH,mod,Y
6.2 Sliding and sum of velocities
6.3 Local relative lubricating film thickness, λz,Y
6.4 Local coefficient of friction, μY

7 Local contact temperature, θC,Y

7.1 General
7.2 Power losses influencing the bulk temperature
7.2.1 General
7.2.2 Method A
7.2.3 Method B
7.2.4 Method C
7.3 Bulk temperature, θM
7.3.1 General
7.3.2 Method A
7.3.3 Method B
7.3.4 Tip relief factor, XCA
7.4 Local flash temperature, θfl,Y

8 Permissible contact temperature

8.1 Limit temperature from scuffing test, θS,DIN
8.2 Permissible temperature, θSC
8.3 Permissible scuffing temperature, θS,Y

9 Local safety factor, SS,Y


Page count: 22