

# ISO/TS 6336-21:2022-05 (E)

## Calculation of load capacity of spur and helical gears - Part 21: Calculation of scuffing load capacity - Integral temperature method

---

### Contents

Page

Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
3.1 Terms and definitions.....	1
3.2 Symbols and units.....	1
<b>4 Field of application.....</b>	<b>4</b>
4.1 General.....	4
4.2 Scuffing damage.....	4
4.3 Integral temperature criterion.....	5
<b>5 Influence factors.....</b>	<b>5</b>
5.1 Mean coefficient of friction, $\mu_{mC}$ .....	5
5.2 Run-in factor, $X_E$ .....	8
5.3 Thermal flash factor, $X_M$ .....	8
5.4 Pressure angle factor, $X_{\alpha\beta}$ .....	9
<b>6 Calculation.....</b>	<b>10</b>
6.1 Cylindrical gears.....	10
6.1.1 General.....	10
6.1.2 Scuffing safety factor, $S_{intS}$ .....	10
6.1.3 Permissible integral temperature, $\vartheta_{intP}$ .....	10
6.1.4 Integral temperature, $\vartheta_{int}$ .....	11
6.1.5 Flash temperature at pinion tooth tip, $\vartheta_{flaE}$ .....	11
6.1.6 Bulk temperature, $\vartheta_M$ .....	11
6.1.7 Mean coefficient of friction, $\mu_{mC}$ .....	12
6.1.8 Run-in factor, $X_E$ .....	12
6.1.9 Thermal flash factor, $X_M$ .....	12
6.1.10 Pressure angle factor, $X_{\alpha\beta}$ .....	12
6.1.11 Geometry factor at tip of pinion, $X_{BE}$ .....	12
6.1.12 Approach factor, $X_Q$ .....	13
6.1.13 Tip relief factor, $X_{Ca}$ .....	14
6.1.14 Contact ratio factor, $X_\epsilon$ .....	15
6.2 Scuffing integral temperature.....	17
6.2.1 General.....	17
6.2.2 Scuffing integral temperature, $\vartheta_{intS}$ .....	18
6.2.3 Relative welding factor, $X_{WrelT}$ .....	22
<b>Annex A (informative) Examples.....</b>	<b>23</b>
<b>Annex B (informative) Contact-time-dependent scuffing temperature.....</b>	<b>32</b>
<b>Bibliography.....</b>	<b>37</b>