

ISO/TS 6336-20:2022-05 (E)

Calculation of load capacity of spur and helical gears - Part 20: Calculation of scuffing load capacity - Flash temperature method

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 Terms and definitions.....	1
3.2 Symbols and units.....	1
4 Scuffing and wear	5
4.1 Occurrence of scuffing and wear.....	5
4.2 Transition diagram.....	5
4.3 Friction at incipient scuffing.....	7
5 Basic formulae	7
5.1 Contact temperature.....	7
5.2 Flash temperature formula.....	8
5.3 Transverse unit load.....	10
5.4 Distribution of overall bulk temperatures.....	11
5.5 Rough approximation of a bulk temperature.....	11
6 Coefficient of friction	12
6.1 General.....	12
6.2 Mean coefficient of friction, method A.....	12
6.3 Mean coefficient of friction, method B.....	13
6.4 Mean coefficient of friction, method C.....	13
7 Parameter on the line of action	14
8 Approach factor	15
9 Load sharing factor, X_{Γ}	15
9.1 General.....	15
9.2 Spur gears with unmodified profiles.....	16
9.3 Spur gears with profile modification.....	17
9.4 Buttressing factor, $X_{\text{but},\Gamma}$	18
9.5 Helical gears with $\varepsilon_{\beta} \leq 0,8$ and unmodified profiles.....	19
9.6 Helical gears with $\varepsilon_{\beta} \leq 0,8$ and profile modification.....	19
9.7 Helical gears with $\varepsilon_{\beta} \geq 1,2$ and unmodified profiles.....	20
9.8 Helical gears with $\varepsilon_{\beta} \geq 1,2$ and profile modification.....	21
9.9 Helical gears with $0,8 < \varepsilon_{\beta} < 1,2$	22
10 Scuffing temperature and safety	23
10.1 Scuffing temperature.....	23
10.2 Structural factor.....	23
10.3 Contact exposure time.....	24
10.4 Scuffing temperature in gear tests.....	25
10.5 Safety range.....	25
Annex A (informative) Flash temperature formula presentation	26
Annex B (informative) Optimal profile modification	31
Bibliography	33