

ISO 21815-3:2023-08 (E)

Earth-moving machinery - Collision warning and avoidance - Part 3: Risk area and risk level for forward/reverse motion

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Performance requirements	7
4.1 General requirements	7
4.2 Calculating CxS distance	7
4.2.1 Forward/reverse motion	7
4.2.2 Collision risk area reduction	7
4.3 Determination of collision risk level	8
4.4 Collision warning and collision avoidance action	8
4.5 CxS action and expected machine speed behaviour	8
4.5.1 General	8
4.5.2 Requirement of D0	8
4.5.3 CxS configuration	8
4.6 Collision warning system	9
4.6.1 System functionality	9
4.6.2 Discontinuation of warning signal and reactivation	9
4.6.3 Human interface requirements	9
4.7 Collision avoidance system	10
4.7.1 System functionality	10
4.7.2 Discontinuation of collision avoidance action and reactivation	10
4.7.3 Intervention indicator	11
5 Time and distance calculation guidance	11
5.1 General	11
5.2 CxS detection, determination and communication	11
5.3 Action time (TCD) and action distance (DCD)	11
5.4 CWS action time (TCD)	12
6 Information for use	12
6.1 General	12
6.2 Operator's manual	12
Annex A (normative) Determining of collision risk levels -- forward/reverse motion	13
Annex B (normative) Limitations of use of CxS	16
Annex C (informative) Example calculation CxS distance for surface vehicles	22
Annex D (informative) Example calculations of CxS distance for underground mining machine	24
Annex E (informative) Estimating the path	34
Annex F (informative) An approach for determining CxS configuration	38

Annex G (informative) Types of interventional collision avoidance actions	44
Bibliography	48