

ISO 10300-2:2023-08 (E)

Calculation of load capacity of bevel gears - Part 2: Calculation of surface durability (macropitting)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols, general subscripts and abbreviated terms | 2 |
| 5 | Macropitting damage -- General aspects | 6 |
| 5.1 | Acceptable versus unacceptable macropitting | 6 |
| 5.2 | Assessment requirements | 6 |
| 5.3 | General rating procedure | 7 |
| 6 | Gearflank rating formulae--Method B1 | 7 |
| 6.1 | Contact stress formula | 7 |
| 6.2 | Permissible contact stress | 8 |
| 6.3 | Calculated safety factor for contact stress | 8 |
| 6.4 | Contact stress factors | 9 |
| 6.4.1 | Mid-zone factor, ZM-B | 9 |
| 6.4.2 | Load sharing factor, ZLS | 10 |
| 6.5 | Permissible contact stress factors | 11 |
| 6.5.1 | Bevel gear factor, ZKP | 11 |
| 6.5.2 | Size factor, ZX | 12 |
| 6.5.3 | Hypoid factor, ZHyp | 12 |
| 7 | Gearflank rating formulae--Method B2 | 15 |
| 7.1 | Contact stress formula | 15 |
| 7.2 | Permissible contact stress | 16 |
| 7.3 | Calculated safety factor for contact stress | 16 |
| 7.4 | Contact stress factors | 16 |
| 7.4.1 | General | 16 |
| 7.4.2 | Macropitting resistance geometry factor, ZI | 17 |
| 7.4.3 | Facewidth factor, ZFW | 20 |
| 7.4.4 | Contact stress adjustment factor, ZA | 20 |
| 8 | Factors for contact stress and permissible contact stress common for method B1 and method B2 | 21 |
| 8.1 | Elasticity factor, ZE | 21 |
| 8.2 | Lubricant film influence factors, ZL, Zv, ZR | 21 |
| 8.2.1 | General | 21 |
| 8.2.2 | Restrictions | 21 |
| 8.2.3 | Method B | 21 |
| 8.2.4 | Method C (product of ZL, Zv and ZR) | 23 |
| 8.3 | Work hardening factor, ZW | 23 |
| 8.3.1 | General | 23 |
| 8.3.2 | Work hardening factor, ZW: Method A | 23 |
| 8.3.3 | Work hardening factor, ZW: Method B | 24 |

| | | |
|---|------------------------|----|
| 8.4 | Life factor, ZNT | 26 |
| 8.4.1 | General | 26 |
| 8.4.2 | Method A | 27 |
| 8.4.3 | Method B | 28 |
| Annex A (informative)Localcalculationmethodforsurfacedurability(macropitting)- MethodB1- localised | | 29 |
| Bibliography | | 35 |