ISO 21360-5:2023-11 (E)

Vacuum technology - Standard methods for measuring vacuum-pump performance - Part 5: Non-evaporable getter (NEG) vacuum pumps

Contents

Page

Foreword ..... **iv**

Introduction ..... **v**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Symbols and abbreviated terms **3**

5 Test methods **4**

5.1 General 4

5.1.1 Test gases 4

5.1.2 Vacuum chamber 4

5.1.3 Orifice 4

5.1.4 Vacuum pumping system for rough pumping 4

5.1.5 Vacuum gauges 5

5.1.6 Temperature 5

5.1.7 Activation method of NEG 5

5.1.8 Procedure of sample installation and activation 5

5.2 Throughput method for small NEG samples 6

5.2.1 Experimental setup 6

5.2.2 Sample 7

5.2.3 Determination of getter pumping speed, S, and sorption quantity, C_q 7

5.2.4 Determination of sticking probability, α 10

5.2.5 Measurement procedure 10

5.2.6 Measurement uncertainty 11

5.3 Throughput method with test dome 11

5.3.1 Experimental setup 11

5.3.2 Sample 13

5.3.3 Determination of getter pumping speed S and sorption quantity, C_q 13

5.3.4 Determination of sticking probability, α 13

5.3.5 Measurement procedure 13

5.3.6 Measurement uncertainty 14

5.4 Transmission method for NEG coatings 14

5.4.1 Experimental setup 14

5.4.2 Sample 15

5.4.3 Determination of average getter pumping speed per unit area, S_A, and sorption quantity C_q 15

5.4.4 Determination of sticking probability, α 16

5.4.5 Measurement procedure 16

5.4.6 Measurement uncertainty 17

5.5 Combination of transmission method and throughput method with test dome 17

6 Reporting **18**

6.1 General 18

6.2 Small size of NEGs with the structure of pill, disk, ring, strip, module and cartridge 18

6.3 NEG pumps 19

6.4 NEG coatings 19

Annex A (informative) **Calculation method of the molecular conductance of the orifice** **21**

Annex B (informative) **Example of diagrams for pumping characteristics of NEG** **22**

Annex C (informative) **Typical value of initial sticking probability α_0 of NEG at room temperature** **23**

Bibliography **25**