ISO 11619:2024-07 (E)

Pneumatic fluid power - Polyurethane and polyamide tubings for use primarily in pneumatic installations - Dimensions and specification

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Materials and construction 1

5 Dimensions and tolerances 2
5.1 Outside and inside diameters, wall thickness and tolerances 2
5.1.1 Polyurethane tubing 2
5.1.2 Polyamide tubings 3
5.1.3 Length tolerances 4

6 Performance requirements 4
6.1 Hydrostatic testing at 23 °C ± 2 °C 4
6.1.1 General 4
6.1.2 Polyurethane tubing hydrostatic testing 4
6.2 Polyamide hydrostatic testing 5
6.3 Hydrostatic testing at high temperature 6
6.3.1 General 6
6.3.2 Polyurethane hydrostatic testing 6
6.3.3 Polyamide hydrostatic testing 7
6.4 Maximum working pressure 8
6.4.1 Polyurethane tubing 8
6.4.2 Polyamide tubing 9
6.5 Minimum bend radius 10
6.5.1 Polyurethane tubing bending radius 10
6.5.2 Polyamide tubing bending radius 11
6.6 UV ageing testing 12

7 Type, routine and production testing 12

8 Marking 12

9 Recommendations for packing and storage 12

Annex A (normative) Test frequency 13

Bibliography 14