

# ISO 11619:2024-07 (E)

## Pneumatic fluid power - Polyurethane and polyamide tubings for use primarily in pneumatic installations - Dimensions and specification

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Materials and construction .....	1
5	Dimensions and tolerances .....	2
5.1	Outside and inside diameters, wall thickness and tolerances .....	2
5.1.1	Polyurethane tubing .....	2
5.1.2	Polyamide tubings .....	3
5.1.3	Length tolerances .....	4
6	Performance requirements .....	4
6.1	Hydrostatic testing at 23 °C ± 2 °C .....	4
6.1.1	General .....	4
6.1.2	Polyurethane tubing hydrostatic testing .....	4
6.2	Polyamide hydrostatic testing .....	5
6.3	Hydrostatic testing at high temperature .....	6
6.3.1	General .....	6
6.3.2	Polyurethane hydrostatic testing .....	6
6.3.3	Polyamide hydrostatic testing .....	7
6.4	Maximum working pressure .....	8
6.4.1	Polyurethane tubing .....	8
6.4.2	Polyamide tubing .....	9
6.5	Minimum bend radius .....	10
6.5.1	Polyurethane tubing bending radius .....	10
6.5.2	Polyamide tubing bending radius .....	11
6.6	UV ageing testing .....	12
7	Type, routine and production testing .....	12
8	Marking .....	12
9	Recommendations for packing and storage .....	12
Annex A (normative)	Test frequency .....	13
Bibliography .....		14