

# ISO 24477:2025-03 (E)

## Vacuum technology - Vacuum gauges - Specifications, calibration and measurement uncertainties for spinning rotor gauges

---

Contents		Page
Foreword		iv
Introduction		v
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>1</b>
3.1	Terms related to components	2
3.2	Terms related to physical parameters	2
<b>4</b>	<b>Symbols and abbreviated terms</b>	<b>4</b>
<b>5</b>	<b>Principle of a spinning rotor gauge</b>	<b>4</b>
<b>6</b>	<b>Specifications for spinning rotor gauge</b>	<b>5</b>
6.1	Diameter and density of rotor	5
6.2	Materials of rotor and thimble	5
6.3	Connecting flange of thimble	6
6.4	Leak rate of thimble with flange	6
6.5	Suspension head positioning	6
6.6	Limits of rotor frequency	6
6.7	Warm-up period	6
6.8	Baking temperature	6
6.9	Measurement range	6
6.10	Sampling time	6
6.11	Internal volume	6
6.12	Interface and pin connections of controller	6
6.13	Dimensions and weights of suspension head and controller	6
6.14	Display and signal output	6
6.15	Nominal operating (environment) conditions	7
6.16	Storage and transportation conditions	7
6.17	Input power and electrical requirements	7
6.18	Number of display digits	7
<b>7</b>	<b>Additional (optional) specifications for spinning rotor gauge</b>	<b>7</b>
7.1	Long-term instability	7
7.2	Expected measurement uncertainty	7
7.3	Compatibility between a suspension head and a rotor	7
7.4	Inspection record and calibration certificate	7
7.5	Allowed vibration level	7
7.6	Cable length	8
7.7	Photograph	8
<b>8</b>	<b>Calibration</b>	<b>8</b>
8.1	Parameters to be calibrated	8
8.2	Calibration procedures	8
8.2.1	General	8
8.2.2	Calibration method A for $\sigma_{\text{eff},0}$	9
8.2.3	Calibration method B for $\sigma_{\text{eff},0}$	9
8.3	Calibration uncertainty	10
8.4	Calibration certificate	10
<b>9</b>	<b>Measurement uncertainty at use</b>	<b>10</b>
<b>Bibliography</b>		<b>11</b>