

DIN EN ISO 19932-2:2026-08 (E)

Equipment for crop protection - Knapsack sprayers - Part 2: Test methods (ISO 19932-2:2025)

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test liquids and equipment	1
5 General	2
5.1 Test conditions	2
5.2 Sprayer	2
5.3 Functional tests	3
5.3.1 Spray liquid shut-off device reliability	3
5.3.2 Spray liquid output	3
5.3.3 Load carrying straps and their fixation points	3
5.3.4 Stability	3
5.3.5 Contents gauge scale and total volume	3
5.3.6 Filling rate	4
5.3.7 Emptying	4
5.3.8 Absorbency of harness	5
5.4 Pressure test	5
5.5 Leakage test	5
5.6 Centre of gravity	6
6 Specific tests for lever-operated knapsack sprayers	7
6.1 Preconditioning	7
6.2 Volume of the external surface deposit	7
6.3 Volume of total residual liquid	8
6.4 Drop test	8
7 Specific tests for engine- or motor-driven knapsack sprayers	9
7.1 Volume of external surface deposit	9
7.2 Volume of total residual liquid	9
8 Specific tests for compression sprayers	10
8.1 Volume test	10
8.1.1 Volume of external surface deposit	10
8.1.2 Volume of total residual liquid	10
8.2 Drop test	10
9 Test report	11
Annex A (informative) Example of a preconditioning device	12
Annex B (informative) Example of a spray liquid shut-off test device	13
Annex C (informative) Example of a strap test device	14
Annex D (informative) Example of drop test device	15
Annex E (informative) Example of filling device	17
Annex F (informative) Example of test report	18