

DIN EN ISO 16122-4:2026-05 (E)

Agricultural and forestry machines - Inspection of sprayers in use - Part 4: Fixed and semi-mobile sprayers (ISO 16122-4:2024)

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Requirements and method of verification	1
4.1	General	1
4.2	Leaks and dripping	2
4.2.1	Static leaks	2
4.2.2	Dynamic leaks	2
4.2.3	Spraying and dripping on parts	2
4.3	Pump(s)	2
4.3.1	Capacity	2
4.3.2	Pulsations	3
4.3.3	Air chamber	3
4.4	Spray mix agitation	3
4.4.1	Hydraulic	3
4.4.2	Mechanical	3
4.5	Spray tank(s)	4
4.5.1	Lid	4
4.5.2	Tank filling strainer(s)	4
4.5.3	Pressure compensation	4
4.5.4	Tank content indicator(s)	4
4.5.5	Tank emptying	4
4.5.6	Tank filling	4
4.5.7	Induction hopper	4
4.5.8	Cleaning device for plant protection product containers	5
4.5.9	Cleaning equipment	5
4.6	Measuring systems, controls and regulation systems	5
4.6.1	General	5
4.6.2	Pressure indicator for spray liquid	5
4.6.3	Other measuring devices	6
4.6.4	Pressure adjusting devices	6
4.6.5	Direct injection systems	6
4.7	Lines (pipes and hoses)	7
4.7.1	Lines	7
4.8	Filters	7
4.8.1	Filter presence	7
4.8.2	Isolating device	7
4.8.3	Filter insert changeability	7
4.9	Application unit	7
4.9.1	Dripping	7
4.9.2	Horizontal spray booms	7
4.9.3	Vertical spray boom	9
4.9.4	Spray guns and lances	10
4.10	Blower	10
4.10.1	Condition	10
4.10.2	Adjustability	10
4.11	Distribution	10

4.11.1	Uniformity of spray jet.....	10
4.11.2	Nozzle output.....	11
4.11.3	Spray distribution measurement on a patternator (optional).....	11
4.11.4	Optional vertical distribution information.....	11
4.12	Autonomous application units.....	11
4.12.1	Drive system.....	11
4.12.2	Travel speed spray robots.....	12
4.13	Cleaning equipment.....	12
5	Test methods.....	12
5.1	Test facilities and equipment.....	12
5.1.1	General.....	12
5.1.2	Test facilities.....	12
5.2	Spray agitation pumps.....	12
5.2.1	Pump capacity test.....	12
5.2.2	Pump pulsations.....	14
5.3	Sprayer's pressure indicators.....	14
5.3.1	Specification of pressure indicators used for verification.....	14
5.3.2	Verification method of the sprayer pressure indicator.....	14
5.4	Flow meters for controlling the volume/area rate.....	15
5.4.1	General.....	15
5.4.2	Operating procedure No. 1: Verification by nozzle flow rate measurement.....	15
5.4.3	Operating Procedure No. 2: Verification by installing a calibrated flow meter in the circuit of the sprayer.....	15
5.5	System for controlling forward speed.....	15
5.6	Uniformity of the transverse volume distribution with a horizontal patternator.....	15
5.6.1	Specification of the horizontal patternators used for verification.....	15
5.6.2	Calculation of coefficient of variation (C_V).....	16
5.6.3	Verification method of the uniformity of the transverse distribution.....	16
5.6.4	Verification method of spray gun/lance flow rate.....	16
5.7	Flow rate of the spray nozzles.....	16
5.7.1	General.....	16
5.7.2	Measurement with nozzles fitted on the sprayer.....	17
5.7.3	Measurement with nozzles removed from the sprayer.....	17
5.8	Pressure drop.....	17
5.9	Pressure variation when the sections are closed.....	17
5.10	Pressure variation when the spray is switched off.....	17
5.11	Accuracy of direct injection systems.....	17
5.12	Pressure distribution.....	18
	Bibliography.....	19