

ISO 10303-511:2001-04 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 511: Application interpreted construct: Topologically bounded surface

Contents		Page
1	Scope	1
2	Normative references	2
3	Terms, definitions and abbreviations	2
3.4	Other definitions	3
3.5	Abbreviations	4
4	EXPRESS short listing	4
4.1	Fundamental concepts and assumptions	6
4.2	aic topologically bounded surface schema entity definition: advanced face	8
	Annex A (normative) Short names of entities	12
	Annex B (normative) Information object registration	13
B.1	Document identification	13
B.2	Schema identification	13
	Annex C (informative) Computer-interpretable listings	14
	Annex D (informative) EXPRESS-G diagrams	15
	Index	24
	Figures Figure D.1 aic topologically bounded surface EXPRESS-G diagram page 1 of 8	16
	Figure D.2 aic topologically bounded surface EXPRESS-G diagram page 2 of 8	17
	Figure D.3 aic topologically bounded surface EXPRESS-G diagram page 3 of 8	18
	Figure D.4 aic topologically bounded surface EXPRESS-G diagram page 4 of 8	19
	Figure D.5 aic topologically bounded surface EXPRESS-G diagram page 5 of 8	20
	Figure D.6 aic topologically bounded surface EXPRESS-G diagram page 6 of 8	21
	Figure D.7 aic topologically bounded surface EXPRESS-G diagram page 7 of 8	22
	Figure D.8 aic topologically bounded surface EXPRESS-G diagram page 8 of 8	23
	Tables Table A.1 Short names of entities	12