

ISO/TR 14179-1:2001-07 (E)

Gears - Thermal capacity - Part 1: Rating gear drives with thermal equilibrium at 95 °C sump temperature

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Symbols and units, term and definition | 1 |
| 3 | Rating criteria | 4 |
| 4 | Service conditions | 5 |
| 4.1 | Intermittent service | 5 |
| 4.2 | Adverse conditions | 5 |
| 4.3 | Favourable conditions | 5 |
| 4.4 | Auxiliary cooling | 5 |
| 5 | Methods for determining the thermal rating | 6 |
| 6 | Method A -- Test | 6 |
| 7 | Method B -- Calculations for determining the thermal power rating, PT | 6 |
| 7.1 | Basis | 6 |
| 7.2 | Heat generation | 7 |
| 7.3 | Bearing power loss, PB | 7 |
| 7.4 | Mesh power loss, PM, spur and helical gears | 11 |
| 7.5 | Mesh power loss, PM, bevel gears | 14 |
| 7.6 | Mesh power loss, PM, cylindrical worm gears | 14 |
| 7.7 | Mesh power loss, PM, double enveloping worm gears | 14 |
| 7.8 | Oil seal power loss, PS | 14 |
| 7.9 | Gear windage and churning power loss, PW | 15 |
| 7.10 | Bearing windage and churning power loss, PWB | 16 |
| 7.11 | Oil pump power loss, PP | 19 |
| 7.12 | Heat dissipation, PQ | 20 |
| 8 | Modifications for non-standard operating conditions | 21 |
| Annex A (informative) Bevel gear mesh and gear windage power losses | | 24 |
| Annex B (informative) Worm gear mesh power losses | | 28 |
| Bibliography | | 30 |