

# ISO 3968:2001-12 (E)

## Hydraulic fluid power - Filters - Evaluation of differential pressure versus flow characteristics

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols .....</b>	<b>2</b>
<b>4.1</b>	<b>Literal symbols .....</b>	<b>2</b>
<b>4.2</b>	<b>Graphical symbols .....</b>	<b>2</b>
<b>5</b>	<b>Test equipment .....</b>	<b>2</b>
<b>5.1</b>	<b>General indications .....</b>	<b>2</b>
<b>5.2</b>	<b>Pump .....</b>	<b>2</b>
<b>5.3</b>	<b>Reservoir .....</b>	<b>3</b>
<b>5.4</b>	<b>Temperature control .....</b>	<b>4</b>
<b>5.5</b>	<b>Clean-up filter .....</b>	<b>4</b>
<b>5.6</b>	<b>Sampling valve .....</b>	<b>4</b>
<b>5.7</b>	<b>Mounting of filter .....</b>	<b>4</b>
<b>5.8</b>	<b>Test fluid .....</b>	<b>4</b>
<b>6</b>	<b>Measurements .....</b>	<b>4</b>
<b>6.1</b>	<b>Pressure measurement .....</b>	<b>4</b>
<b>6.2</b>	<b>Temperature measurement .....</b>	<b>5</b>
<b>6.3</b>	<b>Kinematic viscosity measurement .....</b>	<b>5</b>
<b>6.4</b>	<b>Flow rate measurement .....</b>	<b>5</b>
<b>6.5</b>	<b>Fluid cleanliness measurement .....</b>	<b>6</b>
<b>6.6</b>	<b>Accuracy of measuring instruments and test conditions .....</b>	<b>6</b>
<b>7</b>	<b>Procedure .....</b>	<b>6</b>
<b>7.1</b>	<b>Pipework correction .....</b>	<b>6</b>
<b>7.2</b>	<b>Cleanliness of test circuit .....</b>	<b>6</b>
<b>7.3</b>	<b>Characteristics of the filter housing .....</b>	<b>6</b>
<b>7.4</b>	<b>Characteristics of the filter assembly .....</b>	<b>7</b>
<b>7.5</b>	<b>Characteristics of the filter element only .....</b>	<b>7</b>
<b>7.6</b>	<b>Characteristics of the bypass valve .....</b>	<b>7</b>
<b>8</b>	<b>Presentation of results .....</b>	<b>8</b>
<b>9</b>	<b>Identification statement (Reference to this International Standard) .....</b>	<b>10</b>
Bibliography .....		11