ISO 10303-216:2003-08 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 216: Application protocol: Ship m oulded forms

Contents

Page

1 Scope 1

2 Normative references 3

3 Terms, definitions and abbreviations 4
3.4 Other terms and definitions 6
3.5 Abbreviations 13

4 Information requirements 13
4.1 Units of functionality 14
4.1.1 basic_geometry 15
4.1.2 configuration_management 15
4.1.3 definitions 16
4.1.4 external_references 16
4.1.5 hull_class_applicability 17
4.1.6 hydrostatics 17
4.1.7 items 18
4.1.8 location_concepts 18
4.1.9 offset_table_representations 19
4.1.10 ship_design_parameter 20
4.1.11 ship_general_characteristics 20
4.1.12 ship_measures 21
4.1.13 ship_moulded_forms 21
4.1.14 surface_representations 22
4.1.15 wireframe_representations 22
4.2 Application objects 23
4.3 Application assertions 163

5 Application interpreted model 180
5.1 Mapping specification 180
5.2 AIM EXPRESS short listing 394

6 Conformance requirements 601

Annex A (normative) AIM EXPRESS expanded listing 612

Annex B (normative) AIM short names 788

Annex C (normative) Implementation method specific requirements 797

Annex D (normative) Protocol Implementation Conformance Statement (PICS) proforma 798

Annex E (normative) Information object registration 800

Annex F (informative) Application activity model 801

Annex G (informative) Application reference model 828

Annex H (informative) AIM EXPRESS-G 854

Annex J (informative) Computer interpretable listings 881

Annex K (informative) Application protocol usage guide **882**

Annex L (informative) Technical discussions **883**

Bibliography **900**

Index **901**

Figures Figure 1 -- Shipbuilding application protocols ..... **x**

Figure 2 -- Data planning model ..... **xii**

Figure 3 -- Ship moulded forms overview **1**

Figure 4 -- Bilge keel **26**

Figure 5 -- Shaft bossings **27**

Figure 6 -- Shaft strut **28**

Figure 7 -- Shaft struts **29**

Figure 8 -- Keel dimensions **33**

Figure 9 -- Dimensions of the bulbous bow **35**

Figure 10 -- Global axis placements **58**

Figure 11 -- Transverse meta- centre **68**

Figure 12 -- Measuring shell thickness **70**

Figure 13 -- Local coordinate system **74**

Figure 14 -- Midship tumble **76**

Figure 15 -- Ship hull with bulbous bow and thruster tunnels **79**

Figure 16 -- Ship hull with bulbous bow **83**

Figure 17 -- Bulkheads and decks **84**

Figure 18 -- Double bottom **85**

Figure 19 -- Outer and inner bottom with profiles **85**

Figure 20 -- Double ship hull **86**

Figure 21 -- Frames and decks **87**

Figure 22 -- Girders **88**

Figure 23 -- Rudder and propeller **89**

Figure 24 -- Screw propeller model **89**

Figure 25 -- Thruster **90**

Figure 26 -- Decks and superstructure **90**

Figure 27 -- Transom stern **91**

Figure 28 -- Transverse bulkheads 91

Figure 29 -- Vertical axis propeller 102

Figure 30 -- Vertical axis propeller technology 103

Figure 31 -- Propeller location 104

Figure 32 -- Propeller dimensions 105

Figure 33 -- Controllable propeller blade 108

Figure 34 -- Fixed propeller blade 109

Figure 35 -- Ducted propeller 110

Figure 36 -- Controllable screw propeller 112

Figure 37 -- Rudder dimensions 114

Figure 38 -- Ship curves 119

Figure 39 -- Buttock lines 120

Figure 40 -- Station lines 122

Figure 41 -- Waterlines 122

Figure 42 -- Ship hull, rudder and propeller 126

Figure 43 -- Ship hull dimensions 128

Figure 44 -- Ship points 130

Figure 45 -- Ship types 141

Figure 46 -- Ship types 142

Figure 47 -- Spacing position 146

Figure 48 -- Surface representation 151

Figure 49 -- Thruster propeller 152

Figure 50 -- Form stability 153

Figure 51 -- Wireframe 159

Figure F.1 -- IDEF0 Basic notation 801

Figure F.2 -- Node A0 - moulded form life cycle 814

Figure F.3 -- Node A0 - perform ship life cycle 815

Figure F.4 -- Node A1 - specify ship 816

Figure F.5 -- Node A12 - prepare bid 817

Figure F.6 -- Node A122 - create preliminary design 818

Figure F.7 -- Node A1221 - create preliminary hull form 819

Figure F.8 -- Node A12214 - generate initial hull form definition 820

Figure F.9 -- Node A1223 - estimate hydrodynamics and powering 821

Figure F.10 -- Node 12231 - estimate resistance and powering 822

Figure F.11 -- Node A2 - complete and approve ship design 823

Figure F.12 -- Node A22 - finalize and approve hull form 824

Figure F.13 -- Node A23 - finalize and approve hydrodynamics and powering 825

Figure F.14 -- Node A3 - produce and inspect a ship 826

Figure F.15 -- Node A34 - test ship 827

Figure G.1 -- ARM EXPRESS-G diagram 1 of 25 829

Figure G.2 -- ARM EXPRESS-G diagram 2 of 25 830

Figure G.3 -- ARM EXPRESS-G diagram 3 of 25 831

Figure G.4 -- ARM EXPRESS-G diagram 4 of 25 832

Figure G.5 -- ARM EXPRESS-G diagram 5 of 25 833

Figure G.6 -- ARM EXPRESS-G diagram 6 of 25 834

Figure G.7 -- ARM EXPRESS-G diagram 7 of 25 835

Figure G.8 -- ARM EXPRESS-G diagram 8 of 25 836

Figure G.9 -- ARM EXPRESS-G diagram 9 of 25 837

Figure G.10 -- ARM EXPRESS-G diagram 10 of 25 838

Figure G.11 -- ARM EXPRESS-G diagram 11 of 25 839

Figure G.12 -- ARM EXPRESS-G diagram 12 of 25 840

Figure G.13 -- ARM EXPRESS-G diagram 13 of 25 841

Figure G.14 -- ARM EXPRESS-G diagram 14 of 25 842

Figure G.15 -- ARM EXPRESS-G diagram 15 of 25 843

Figure G.16 -- ARM EXPRESS-G diagram 16 of 25 844

Figure G.17 -- ARM EXPRESS-G diagram 17 of 25 845

Figure G.18 -- ARM EXPRESS-G diagram 18 of 25 846

Figure G.19 -- ARM EXPRESS-G diagram 19 of 25 847

Figure G.20 -- ARM EXPRESS-G diagram 20 of 25 848

Figure G.21 -- ARM EXPRESS-G diagram 21 of 25 849

Figure G.22 -- ARM EXPRESS-G diagram 22 of 25 850

Figure G.23 -- ARM EXPRESS-G diagram 23 of 25 851

Figure G.24 -- ARM EXPRESS-G diagram 24 of 25 852
Figure G.25 -- ARM EXPRESS-G diagram 25 of 25 853
Figure H.1 -- application context - AIM diagram 1 of 26 in EXPRESS-G 855
Figure H.2 -- product definition - AIM diagram 2 of 26 in EXPRESS-G 856
Figure H.3 -- property definition - AIM diagram 3 of 26 in EXPRESS-G 857
Figure H.4 -- representation - AIM diagram 4 of 26 in EXPRESS-G 858
Figure H.5 -- action - AIM diagram 5 of 26 in EXPRESS-G 859
Figure H.6 -- person and organization - AIM diagram 6 of 26 in EXPRESS-G 860
Figure H.7 -- person and organization assignment - AIM diagram 7 of 26 in EXPRESS-G 861
Figure H.8 -- approval - AIM diagram 8 of 26 in EXPRESS-G 862
Figure H.9 -- date and time - AIM diagram 9 of 26 in EXPRESS-G 863
Figure H.10 -- classification assignment and group - AIM diagram 10 of 26 in EXPRESS-G 864
Figure H.11 -- identification assignment external source - AIM diagram 11 of 26 in EXPRESS-G 865
Figure H.12 -- document - AIM diagram 12 of 26 in EXPRESS-G 866
Figure H.13 -- measure with unit - AIM diagram 13 of 26 in EXPRESS-G 867
Figure H.14 -- measure value - AIM diagram 14 of 26 in EXPRESS-G 868
Figure H.15 -- geometric and topological representation - AIM diagram 15 of 26 in EXPRESS-G 869
Figure H.16 -- point - AIM diagram 16 of 26 in EXPRESS-G 870
Figure H.17 -- placement - AIM diagram 17 of 26 in EXPRESS-G 871
Figure H.18 -- curve - AIM diagram 18 of 26 in EXPRESS-G 872
Figure H.19 -- bounded curve - AIM diagram 19 of 26 in EXPRESS-G 873
Figure H.20 -- surface - AIM diagram 20 of 26 in EXPRESS-G 874
Figure H.21 -- elementary surfaceAIM diagram 21 of 26 in EXPRESS-G 875
Figure H.22 -- bounded surface - AIM diagram 22 of 26 in EXPRESS-G 876
Figure H.23 -- solid model and shell - AIM diagram 23 of 26 in EXPRESS-G 877
Figure H.24 -- topology - AIM diagram 24 of 26 in EXPRESS-G 878
Figure H.25 -- name attribute and role association - AIM diagram 25 of 26 in EXPRESS-G 879
Figure H.26 -- id and description attribute - AIM diagram 26 of 26 in EXPRESS-G 880
Figure L.1 -- Ship Product Model 884
Figure L.3 -- Modeling framework 888
Figure L.4 -- Life cycle concept 889

Figure L.5 -- Redeclaration of attributes 889

Tables Table 1 -- Key mappings for AP216 181

Table 2 -- Conformance classes 602

Table 3 -- Conformance class elements 602

Table B.1 -- AIM short names of entities 788

Table L.7 -- ARM measures and corresponding AIM measures and units 891