

ISO 10303-216:2003-08 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 216: Application protocol: Ship moulded forms

Contents		Page
1	Scope	1
2	Normative references	3
3	Terms, definitions and abbreviations	4
3.4	Other terms and definitions	6
3.5	Abbreviations	13
4	Information requirements	13
4.1	Units of functionality	14
4.1.1	basic_geometry	15
4.1.2	configuration_management	15
4.1.3	definitions	16
4.1.4	external_references	16
4.1.5	hull_class_applicability	17
4.1.6	hydrostatics	17
4.1.7	items	18
4.1.8	location_concepts	18
4.1.9	offset_table_representations	19
4.1.10	ship_design_parameter	20
4.1.11	ship_general_characteristics	20
4.1.12	ship_measures	21
4.1.13	ship_moulded_forms	21
4.1.14	surface_representations	22
4.1.15	wireframe_representations	22
4.2	Application objects	23
4.3	Application assertions	163
5	Application interpreted model	180
5.1	Mapping specification	180
5.2	AIM EXPRESS short listing	394
6	Conformance requirements	601
Annex A (normative) AIM EXPRESS expanded listing		612
Annex B (normative) AIM short names		788
Annex C (normative) Implementation method specific requirements		797
Annex D (normative) Protocol Implementation Conformance Statement (PICS) proforma		798
Annex E (normative) Information object registration		800
Annex F (informative) Application activity model		801
Annex G (informative) Application reference model		828
Annex H (informative) AIM EXPRESS-G		854
Annex J (informative) Computer interpretable listings		881

Annex K (informative) Application protocol usage guide	882
Annex L (informative) Technical discussions	883
Bibliography	900
Index	901
Figures Figure 1 -- Shipbuilding application protocols	x
Figure 2 -- Data planning model	xii
Figure 3 -- Ship moulded forms overview	1
Figure 4 -- Bilge keel	26
Figure 5 -- Shaft bossings	27
Figure 6 -- Shaft strut	28
Figure 7 -- Shaft struts	29
Figure 8 -- Keel dimensions	33
Figure 9 -- Dimensions of the bulbous bow	35
Figure 10 -- Global axis placements	58
Figure 11 -- Transverse meta- centre	68
Figure 12 -- Measuring shell thickness	70
Figure 13 -- Local coordinate system	74
Figure 14 -- Midship tumble	76
Figure 15 -- Ship hull with bulbous bow and thruster tunnels	79
Figure 16 -- Ship hull with bulbous bow	83
Figure 17 -- Bulkheads and decks	84
Figure 18 -- Double bottom	85
Figure 19 -- Outer and inner bottom with profiles	85
Figure 20 -- Double ship hull	86
Figure 21 -- Frames and decks	87
Figure 22 -- Girders	88
Figure 23 -- Rudder and propeller	89
Figure 24 -- Screw propeller model	89
Figure 25 -- Thruster	90
Figure 26 -- Decks and superstructure	90
Figure 27 -- Transom stern	91

Figure 28 -- Transverse bulkheads	91
Figure 29 -- Vertical axis propeller	102
Figure 30 -- Vertical axis propeller technology	103
Figure 31 -- Propeller location	104
Figure 32 -- Propeller dimensions	105
Figure 33 -- Controllable propeller blade	108
Figure 34 -- Fixed propeller blade	109
Figure 35 -- Ducted propeller	110
Figure 36 -- Controllable screw propeller	112
Figure 37 -- Rudder dimensions	114
Figure 38 -- Ship curves	119
Figure 39 -- Buttock lines	120
Figure 40 -- Station lines	122
Figure 41 -- Waterlines	122
Figure 42 -- Ship hull, rudder and propeller	126
Figure 43 -- Ship hull dimensions	128
Figure 44 -- Ship points	130
Figure 45 -- Ship types	141
Figure 46 -- Ship types	142
Figure 47 -- Spacing position	146
Figure 48 -- Surface representation	151
Figure 49 -- Thruster propeller	152
Figure 50 -- Form stability	153
Figure 51 -- Wireframe	159
Figure F.1 -- IDEF0 Basic notation	801
Figure F.2 -- Node A0 - moulded form life cycle	814
Figure F.3 -- Node A0 - perform ship life cycle	815
Figure F.4 -- Node A1 - specify ship	816
Figure F.5 -- Node A12 - prepare bid	817
Figure F.6 -- Node A122 - create preliminary design	818
Figure F.7 -- Node A1221 - create preliminary hull form	819

Figure F.8 -- Node A12214 - generate initial hull form definition	820
Figure F.9 -- Node A1223 - estimate hydrodynamics and powering	821
Figure F.10 -- Node 12231 - estimate resistance and powering	822
Figure F.11 -- Node A2 - complete and approve ship design	823
Figure F.12 -- Node A22 - finalize and approve hull form	824
Figure F.13 -- Node A23 - finalize and approve hydrodynamics and powering	825
Figure F.14 -- Node A3 - produce and inspect a ship	826
Figure F.15 -- Node A34 - test ship	827
Figure G.1 -- ARM EXPRESS-G diagram 1 of 25	829
Figure G.2 -- ARM EXPRESS-G diagram 2 of 25	830
Figure G.3 -- ARM EXPRESS-G diagram 3 of 25	831
Figure G.4 -- ARM EXPRESS-G diagram 4 of 25	832
Figure G.5 -- ARM EXPRESS-G diagram 5 of 25	833
Figure G.6 -- ARM EXPRESS-G diagram 6 of 25	834
Figure G.7 -- ARM EXPRESS-G diagram 7 of 25	835
Figure G.8 -- ARM EXPRESS-G diagram 8 of 25	836
Figure G.9 -- ARM EXPRESS-G diagram 9 of 25	837
Figure G.10 -- ARM EXPRESS-G diagram 10 of 25	838
Figure G.11 -- ARM EXPRESS-G diagram 11 of 25	839
Figure G.12 -- ARM EXPRESS-G diagram 12 of 25	840
Figure G.13 -- ARM EXPRESS-G diagram 13 of 25	841
Figure G.14 -- ARM EXPRESS-G diagram 14 of 25	842
Figure G.15 -- ARM EXPRESS-G diagram 15 of 25	843
Figure G.16 -- ARM EXPRESS-G diagram 16 of 25	844
Figure G.17 -- ARM EXPRESS-G diagram 17 of 25	845
Figure G.18 -- ARM EXPRESS-G diagram 18 of 25	846
Figure G.19 -- ARM EXPRESS-G diagram 19 of 25	847
Figure G.20 -- ARM EXPRESS-G diagram 20 of 25	848
Figure G.21 -- ARM EXPRESS-G diagram 21 of 25	849
Figure G.22 -- ARM EXPRESS-G diagram 22 of 25	850
Figure G.23 -- ARM EXPRESS-G diagram 23 of 25	851

Figure G.24 -- ARM EXPRESS-G diagram 24 of 25	852
Figure G.25 -- ARM EXPRESS-G diagram 25 of 25	853
Figure H.1 -- application context - AIM diagram 1 of 26 in EXPRESS-G	855
Figure H.2 -- product definition - AIM diagram 2 of 26 in EXPRESS-G	856
Figure H.3 -- property definition - AIM diagram 3 of 26 in EXPRESS-G	857
Figure H.4 -- representation - AIM diagram 4 of 26 in EXPRESS-G	858
Figure H.5 -- action - AIM diagram 5 of 26 in EXPRESS-G	859
Figure H.6 -- person and organization - AIM diagram 6 of 26 in EXPRESS-G	860
Figure H.7 -- person and organization assignment - AIM diagram 7 of 26 in EXPRESS-G	861
Figure H.8 -- approval - AIM diagram 8 of 26 in EXPRESS-G	862
Figure H.9 -- date and time - AIM diagram 9 of 26 in EXPRESS-G	863
Figure H.10 -- classification assignment and group - AIM diagram 10 of 26 in EXPRESS-G	864
Figure H.11 -- identification assignment external source - AIM diagram 11 of 26 in EXPRESS-G	865
Figure H.12 -- document - AIM diagram 12 of 26 in EXPRESS-G	866
Figure H.13 -- measure with unit - AIM diagram 13 of 26 in EXPRESS-G	867
Figure H.14 -- measure value - AIM diagram 14 of 26 in EXPRESS-G	868
Figure H.15 -- geometric and topological representation - AIM diagram 15 of 26 in EXPRESS-G	869
Figure H.16 -- point - AIM diagram 16 of 26 in EXPRESS-G	870
Figure H.17 -- placement - AIM diagram 17 of 26 in EXPRESS-G	871
Figure H.18 -- curve - AIM diagram 18 of 26 in EXPRESS-G	872
Figure H.19 -- bounded curve - AIM diagram 19 of 26 in EXPRESS-G	873
Figure H.20 -- surface - AIM diagram 20 of 26 in EXPRESS-G	874
Figure H.21 -- elementary surface AIM diagram 21 of 26 in EXPRESS-G	875
Figure H.22 -- bounded surface - AIM diagram 22 of 26 in EXPRESS-G	876
Figure H.23 -- solid model and shell - AIM diagram 23 of 26 in EXPRESS-G	877
Figure H.24 -- topology - AIM diagram 24 of 26 in EXPRESS-G	878
Figure H.25 -- name attribute and role association - AIM diagram 25 of 26 in EXPRESS-G	879
Figure H.26 -- id and description attribute - AIM diagram 26 of 26 in EXPRESS-G	880
Figure L.1 -- Ship Product Model	884
Figure L.3 -- Modeling framework	888
Figure L.4 -- Life cycle concept	889

Figure L.5 -- Redeclaration of attributes	889
Tables Table 1 -- Key mappings for AP216	181
Table 2 -- Conformance classes	602
Table 3 -- Conformance class elements	602
Table B.1 -- AIM short names of entities	788
Table L.7 -- ARM measures and corresponding AIM measures and units	891