

# ISO 10823:2004-02 (E)

## Guidelines for the selection of roller chain drives

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Symbols .....</b>	<b>1</b>
<b>4</b>	<b>Basic equations .....</b>	<b>1</b>
4.1	Input power .....	1
4.2	Corrected power .....	1
<b>5</b>	<b>Drive design specifications .....</b>	<b>2</b>
<b>6</b>	<b>Sprocket selection .....</b>	<b>3</b>
<b>7</b>	<b>Chain calculations and selection .....</b>	<b>3</b>
7.1	Normal operating conditions and drive capacities for chains .....	3
7.2	Correction for other operating conditions for chains .....	7
7.3	Chain selection .....	9
7.4	Chain length .....	9
7.5	Chain speed .....	9
<b>8</b>	<b>Maximum sprocket centre distance .....</b>	<b>10</b>
<b>9</b>	<b>Lubrication .....</b>	<b>11</b>
9.1	Methods of lubrication .....	11
9.2	Oil viscosity .....	12
<b>10</b>	<b>Good practice in drive design .....</b>	<b>12</b>
10.1	Sprocket centre distance .....	12
10.2	Chain adjustment .....	14
10.3	Idlers .....	14
10.4	Drive layout .....	15
<b>Annex A (informative) Example of chain drive selection .....</b>		<b>16</b>
<b>Annex B (informative) Power rating equations .....</b>		<b>19</b>