

ISO 14635-2:2004-04 (E)

Gears - FZG test procedures - Part 2: FZG step load test A10/16, 6R/120 for relative scuffing load-carrying capacity of high EP oils

| Contents | | Page |
|--|-----------------------------------|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Failure criteria | 2 |
| 5 | Brief description of method | 4 |
| 5.1 | General principle | 4 |
| 5.2 | Precision | 4 |
| 6 | Test materials | 4 |
| 6.1 | Test gears | 4 |
| 6.2 | Cleaning fluid | 4 |
| 7 | Apparatus | 4 |
| 7.1 | FZG spur-gear test rig | 4 |
| 7.2 | Heating device | 6 |
| 7.3 | Revolution counter | 6 |
| 7.4 | Balance | 6 |
| 8 | Preparation of apparatus | 8 |
| 9 | Test procedure | 8 |
| 10 | Reporting of results | 10 |
| Annex A (informative) FZG A10-type gear tooth face changes (flank damages) | | 11 |
| Annex B (informative) Typical FZG test report sheet | | 13 |
| Annex C (informative) Checklist for maintenance of FZG gear test rig | | 14 |
| Bibliography | | 19 |