

DIN EN 1151-2:2006-11 (E)

Pumps - Rotodynamic pumps - Circulation pumps having a rated power input not exceeding 200 W for heating installations and domestic hot water installations - Part 2: Noise test code (vibro-acoustics) for measuring structure- and fluid borne noise

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Test rig	7
4.1	General	7
4.2	Main components of test rig	7
4.3	Specification of test rig components	8
4.4	Assembly	11
4.5	Foundation	11
4.6	Qualifications	11
4.7	Instrumentation	11
4.7.1	Measurement of pressure fluctuations	11
4.7.2	Measurement of vibration	11
4.8	Calibration	12
4.8.1	Accelerometers	12
4.8.2	Pressure transducers	12
4.8.3	Calibration of accelerometers and pressure transducers	12
4.9	Propagation factors	12
5	Installation and operation of the tested pump	13
5.1	Installation of the pump	13
5.2	Operating parameters	14
5.3	Initial operation time	14
6	Factors influencing measurements	14
6.1	Electromagnetic surroundings	14
6.2	Earth loops	14
6.3	Vibration surroundings	14
7	Determination of fluid- and structure-borne powers	14
7.1	Frequency range	14
7.2	Measurement parameters	14
7.2.1	Pressure fluctuation measurement parameters	14
7.2.2	Vibration measurement parameters	15
7.3	Sense of power propagation	15
7.4	Fluid-borne power determination	15
7.4.1	General	15
7.4.2	Fluid-borne intensity	15
7.4.3	Fluid-borne power	16
7.5	Structure-borne power determination	16
7.5.1	General	16
7.5.2	Structure-borne intensity	16

7.5.3	Structure-borne power	17
7.6	Overall values of power	17
7.7	Coefficients of energy propagation and power levels	18
7.7.1	Coefficient of fluid-borne energy propagation	18
7.7.2	Coefficient of structure-borne energy propagation	18
7.7.3	Fluid-borne power level	18
7.7.4	Structure-borne power level	18
8	Information to be reported	19
Annex A (informative) Bending wavenumber and intensity dimensional constant		20
Bibliography		21