

# ISO 4156-3:2005-10 (E)

## Straight cylindrical involute splines - Metric module, side fit - Part 3: Inspection

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Symbols and abbreviated terms .....	2
5	Reference conditions .....	3
6	Quality features .....	4
6.1	General .....	4
6.2	Size .....	4
6.3	Location .....	4
6.4	Form .....	5
7	Methods of inspection .....	5
7.1	Size .....	5
7.2	Location .....	7
7.3	Form .....	9
8	Measurements with balls or pins .....	9
8.1	General .....	9
8.2	Selection of balls or pins .....	10
8.3	Use and marking of pins .....	10
8.4	Statistical actual tolerance limit STA .....	10
8.5	Calculation of ball or pin diameter (DRe or DRi) .....	13
8.6	Calculation of dimensions for ball or pin inspection (part and gauge inspection) .....	15
9	Measurement over k teeth -- External splines (W) .....	19
9.1	Calculation of W .....	19
9.2	Choice of k .....	20
10	Gauges .....	21
10.1	Generalities .....	21
10.2	Length of measuring part of gauges .....	22
10.3	Manufacturing tolerances for spline gauges (see Tables 8, 9 and 10) .....	24
10.4	Values of deviation allowances of spline gauges .....	27
10.5	Inspection of gauges .....	27
10.6	Dimensions, designation and marking of gauges .....	29
11	Measurement of spline deviations .....	40
11.1	General .....	40
11.2	Total profile deviation F .....	40
11.3	Total cumulative pitch deviation Fp .....	40
11.4	Total helix deviation F .....	40