

DIN EN 14492-2:2007-04 (E)

Cranes - Power driven winches and hoists - Part 2: Power driven hoists

Contents		Page
Foreword		7
Introduction		8
1	Scope	9
2	Normative references	9
3	Terms and definitions	11
4	List of significant hazards	14
5	Safety requirements and/or protective measures	19
5.1	General	19
5.2	Devices	20
5.3	Couplings	26
5.4	Brakes for hoisting and lowering movements	26
5.5	Gearbox	27
5.6	Load hooks	27
5.7	Rope drives	27
5.8	Chain drives	30
5.9	Belt drives	31
5.10	Pneumatic equipment	32
5.11	Hydraulic equipment	34
5.12	Trolleys	37
5.13	Electrical equipment of hoists and their trolleys	38
5.14	Reduction of noise by design	42
5.15	Hoists for use in a potentially explosive atmosphere	43
6	Verification of the safety requirements and/or protective measures	43
6.1	Hoists manufactured in series	43
6.2	Hoists designed individually	44
7	User information	51
7.1	General	51
7.2	Special requirements	51
7.3	Marking	53
Annex A (informative) Examples of power driven hoists		54
A.1	Rope hoist	54
A.2	Chain hoist	55
A.3	Belt hoist	56
A.4	Open type hoist	57
A.5	NGL building hoists -- Treuil potence de chantier -- Bauaufzüge für nicht geführte Lasten	58
Annex B (normative) Additional requirements when transporting hot molten masses		59
Annex C (informative) Additional requirements for hoists intended to be used in potentially explosion atmosphere		62

C.1	Introduction	62
C.2	General	62
C.3	Hazard sources in explosion hazard areas	63
C.3.1	Electrically caused hazards	63
C.3.2	Mechanically caused hazards	63
C.3.3	Hazards caused by environmental conditions	63
C.3.4	Measures to eliminate hazards in explosion hazard areas	64
C.3.5	Marking	64
C.4	User information	64
Annex D (informative) Additional requirements for operation in aggressive environments and outdoors		65
D.1	General	65
D.2	Ropes and chains	65
Annex E (informative) Additional requirements for operation at low temperatures		67
Annex F (normative) Supporting structures for NGL building hoists		68
F.1	General	68
F.2	Terms and definitions	68
F.3	Classification	69
F.4	Construction characteristics	71
F.4.1	General requirements	71
F.4.2	Interchangeability of parts and modularity	72
F.4.3	Ease of transportation	72
F.5	Calculations	74
F.5.1	General	74
F.5.2	Forces and load combinations to be considered	75
F.5.3	Stability	75
F.5.4	Structural verification	76
F.5.5	Loads transmitted calculations	77
F.6	Instructions	77
F.6.1	Transmitted forces/moments information	77
F.6.2	Markings	80
F.6.3	User information	80
F.7	Verifications	81
Annex G (normative) Power driven series hoist mechanisms - Test procedure for verification of the classification		82
G.1	Introduction	82
G.2	Application	82
G.3	Implementation of the test	82
G.3.1	Framework conditions	82
G.3.2	Configurations	83
G.3.3	Test programme	83
G.4	Acceptance criteria	84
G.5	Calculation and Figures	84
Annex H (informative) Documents for hooks		89
Annex I (informative) Values of IAL, DAL for different types of rated capacity limiters		90
I.1	Calculation of rated capacity limiters	90
Annex J (normative) Selection of motors		92
J.1	General	92
J.2	Criteria for motor selection (EN 60034-1)	92
J.2.1	General	92

J.2.2	Remarks on the selection of motors	93
J.2.3	Degree of protection according to EN 60034-5	93
J.2.4	Thermal calculation of the motor	93
J.2.5	Squirrel cage motor	96
J.2.6	Power correction in function of ambient temperature and altitude	97
J.2.7	Cyclic duration factor and number of working cycles per hour	99
J.3	Motors for vertical motions	99
J.3.1	Determination of required torque	99
J.3.2	Cyclic duration factor and number of cycles per hour	100
J.4	Motors for horizontal motions	102
J.4.1	General	102
J.4.2	Determining the torque necessary	102
J.4.3	Cyclic duration factor and number of cycles per hour	103
J.4.4	Rotation	104
J.4.5	Span variation	104
Annex K (normative) Noise test code		106
K.1	Scope	106
K.2	Standards used in this annex	106
K.3	Description of the machine family	106
K.4	Determination of the emission sound pressure level at the operator's position by measurement	107
K.4.1	General	107
K.4.2	Hoists, other than NGL building hoists	107
K.5	Determination of the sound power level	107
K.5.1	General	107
K.5.2	Hoists, other than NGL building hoists	107
K.5.3	NGL building hoists	108
K.6	Mounting and operation conditions	110
K.6.1	General	110
K.6.2	Hoists, other than NGL building hoists	110
K.6.3	NGL building hoists	110
K.7	Uncertainties	111
K.8	Information to be recorded	111
K.9	Information to be reported	111
K.10	Declaration and verification of noise emission values	111
Annex L (informative) Selection of a suitable set of crane standards for a given application		112
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 98/37/EC		113
Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC		114
Bibliography		115
Figures Figure A.1.1 -- Rope hoist -- Palan à câble -- Seilzug		54
Figure A.1.2.1 -- Monorail trolley, "standard headroom" -- Chariot monorail, "hauteur perdue normale" -- Einschienenuntergurtfahrwerk, "normale Bauhöhe"		54
Figure A.1.2.2 -- Monorail trolley, "short headroom" -- Chariot monorail, "hauteur perdue réduite" -- Einschienenuntergurtfahrwerk, "kurze Bauhöhe"		54
Figure A.1.2.3 -- Crab -- Chariot birail -- Zweischienenobergurtfahrwerk		54
Figure A.1.2 -- Travel carriages (Hoist mounted) -- Chariots (Palan monté) -- Fahrwerke (Hubwerk angebaut)		54
Figure A.2.1 -- Chain hoist -- Palan à chaîne -- Kettenzug		55

Figure A.2.2.1 -- Monorail trolley, "standard headroom" -- Chariot monorail, "hauteur perdue normale" -- Einschienenuntergurtfahrwerk, "normale Bauhöhe"	55
Figure A.2.2.2 -- Monorail trolley, "short headroom" -- Chariot monorail, "hauteur perdue réduite" -- Einschienenuntergurtfahrwerk, "kurze Bauhöhe"	55
Figure A.2.2.3 -- Crab -- Chariot birail -- Zweischienerobergurtfahrwerk	55
Figure A.2.2 -- Travel carriages (Hoist mounted) -- Chariots (Palan monté) -- Fahrwerke (Hubwerk angebaut)	55
Figure A.3.1 -- Belt hoist -- Palan à sangle -- Bandzug	56
Figure A.3.2 -- Monorail trolley -- Chariot monorail -- Einschienenuntergurtfahrwerk	56
Figure A.4 -- Open type hoist -- Treuil ouvert -- Offenes Hubwerk	57
Figure A.5.1 -- Jib hoist with parallel drum -- Treuil potence à tambour parallèle -- Auslegerhubwerk mit paralleler Trommel	58
Figure A.5.2 -- Jib hoist with axial drum -- Treuil potence à tambour axial -- Auslegerhubwerk mit axialer Trommel	58
Figure A.5.3 -- Hoist with trolley -- Treuil potence pour chariot -- Hubwerk mit Fahrwerk	58
Figure A.5.4 -- Suspended hoist -- Treuil potence suspendu -- Aufgehängtes Hubwerk	58
Figure A.5.5 -- Scaffold hoist -- Treuil d'échafaudage -- Gerüstwinde	58
Figure F.1 -- Column support -- Support -- Colonne -- Dreibock	70
Figure F.2 --Jib-extension -- Extension de potence -- Zwischenrahmen	70
Figure F.3 -- Prop support -- Chandelle -- Geschossstütze	70
Figure F.4 -- Window support -- Support fenêtre -- Fensterwinkel	70
Figure F.5 -- Scaffold support -- Support pour échafaudage -- Gerüsthalterung oder -befestigung ...	70
Figure F.6 -- Gantry support -- Chevalet -- Doppelrahmenstütze mit Ausleger	71
Figure F.7 -- Up-jib -- Flèche potence -- Schwenkarm	71
Figure F.8 -- Connection device to the scaffold with T-head bolt	73
Figure F.9 -- Example of hinge with anti pull-out system	73
Figure F.10 -- Connection devices for counterweight and hand rail position	73
Figure F.11 -- Example of jib positioning devices and sheave protection	73
Figure F.12 -- Example of hand lever jib positioning device	73
Figure F.13 -- Self retaining locking handle	73
Figure F.14 -- Rail buffers	74
Figure F.15 -- Feet stop and body guard for gantry support	74
Figure F.16 -- Prop head/length rate	74

Figure F.17 -- Window support hoisting position	74
Figure F.18 -- Transmitted loads from prop support	78
Figure F.19 --Transmitted loads from scaffold support	78
Figure F.20 -- Transmitted loads from up-jib	79
Figure F.21 -- Transmitted loads from window support	79
Figure F.22 -- Transmitted loads from column support	79
Figure F.23 -- Transmitted loads from gantry support	79
Figure G.1 -- Opposed winding arrangement	86
Figure G.2 -- Symmetrical rope lead-off about the drum centre	86
Figure G.3 -- Normal lifting operation during the test (Cycle I)	87
Figure G.4 -- Picking the load up from the floor at the start of every 4 th lifting operation (Cycle II) ..	87
Figure G.5 -- Every 4 th pick up from the floor at main lifting speed, if possible (Cycle III)	87
Figure J.1 -- Torque operation for two different cycles	95
Figure J.2 -- Correction as function of ambient temperature and altitude	98
Figure K.1 -- Microphone positions on the hemisphere	109
Tables Table 1 -- List of significant hazards and associated requirements	15
Table 2 -- Values for hv for estimation of IAL	24
Table 3 -- Speed limit for three-phase slipring motors	40
Table 4 -- Stall torques for three-phase slipring motors with contactor control	41
Table 5 -- Methods to be used to verify conformity with the safety requirements and/or measures ...	45
Table B.1 -- Additional requirements when transporting hot molten masses	61
Table F.1 -- Stability safety factor oS for various forces	75
Table F2 -- Safety coefficients for steel structures	76
Table F.3 -- Load cases	76
Table F.4 -- Means of verification of the safety requirements and/or measures	81
Table I.1 -- Example of values	90
Table J.1 -- Typical operation of torque for 2 different cycles	96
Table J.2 -- Indications for the number of cycles per hour and the cycles duration factor for the vertical motions	101
Table J.3 -- Indications for the number of cycles per hour and the cyclic duration factor for the vertical motions	104
Table K.1 -- Coordinates of the 6 microphone positions	108