

ISO/OECD 789-10:2006-07 (E)

Agricultural tractors - Test procedures - Part 10: Hydraulic power at tractor/implement interface

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Measurement units and tolerances	3
5	General requirements	3
5.1	Specification	3
5.2	Running-in and preliminary adjustments	3
6	Available hydraulic pressure test	4
6.1	Steady state	4
6.1.1	Test conditions	4
6.1.2	Test procedures	5
6.1.2.1	Flow through single coupler pair -- Type 1 tests	5
6.1.2.2	Flow through single coupler pair -- Type 2 tests	5
6.1.2.3	Flow into sump return port with coupler -- Type 2 test	5
6.1.2.4	Flow into sump return port without coupler -- Type 2 test	5
6.2	Peak pressure	5
6.2.1	Test conditions	5
6.2.2	Test procedure -- Maximum flow selected -- Type 2 test	5
6.3	Test report -- Available hydraulic pressure	6
6.3.1	Type 1 tests	6
6.3.2	Type 2 tests	6
7	Available hydraulic power	7
7.1	Test conditions	7
7.2	Test procedures	7
7.2.1	Hydraulic power through single coupler pair -- Types 1 and 2 tests	7
7.2.2	Maximum available hydraulic power using two or more coupler pairs simultaneously -- Types 1 and 2 tests	8
7.3	Test report -- Available hydraulic power	8
7.3.1	Maximum available hydraulic power -- Type 1 tests	8
7.3.2	Maximum useable (continuous) available hydraulic power -- Type 2 tests	8
Annex A (normative)	Specimen test report	10
Bibliography		14