ISO/OECD 789-10:2006-07 (E)

Agricultural tractors - Test procedures - Part 10: Hydraulic power at tractor/implement interface

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Measurement units and tolerances 3

5 General requirements 3
5.1 Specification 3
5.2 Running-in and preliminary adjustments 3

6 Available hydraulic pressure test 4
6.1 Steady state 4
6.1.1 Test conditions 4
6.1.2 Test procedures 5
6.1.2.1 Flow through single coupler pair -- Type 1 tests 5
6.1.2.2 Flow through single coupler pair -- Type 2 tests 5
6.1.2.3 Flow into sump return port with coupler -- Type 2 test 5
6.1.2.4 Flow into sump return port without coupler -- Type 2 test 5
6.2 Peak pressure 5
6.2.1 Test conditions 5
6.2.2 Test procedure -- Maximum flow selected -- Type 2 test 5
6.3 Test report -- Available hydraulic pressure 6
6.3.1 Type 1 tests 6
6.3.2 Type 2 tests 6

7 Available hydraulic power 7
7.1 Test conditions 7
7.2 Test procedures 7
7.2.1 Hydraulic power through single coupler pair -- Types 1 and 2 tests 7
7.2.2 Maximum available hydraulic power using two or more coupler pairs simultaneously -- Types 1 and 2 tests 8
7.3 Test report -- Available hydraulic power 8
7.3.1 Maximum available hydraulic power -- Type 1 tests 8
7.3.2 Maximum useable (continuous) available hydraulic power -- Type 2 tests 8

Annex A (normative) Specimen test report 10

Bibliography 14