

# ISO 6336-6:2006-08 (E)

## Calculation of load capacity of spur and helical gears - Part 6: Calculation of service life under variable load

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviated terms</b> .....	<b>1</b>
<b>4</b>	<b>General</b> .....	<b>1</b>
4.1	Application factors .....	1
4.2	Determination of load and stress spectra .....	1
4.3	General calculation of service life .....	4
4.4	Palmgren-Miner rule .....	5
5.1	Basic principles .....	5
5.2	Calculation of stress spectra .....	7
5.3	Determination of pitting and bending strength values .....	8
5.4	Determination of safety factors .....	8
<b>Annex A (normative) Determination of application factor, <math>K_A</math>, from given load spectrum using equivalent torque, <math>T_{eq}</math></b> .....		<b>10</b>
<b>Annex B (informative) Guide values for application factor, <math>K_A</math></b> .....		<b>15</b>
<b>Annex C (informative) Example calculation of safety factor from given load spectrum</b> .....		<b>18</b>
<b>Bibliography</b> .....		<b>24</b>