

ISO 6336-3:2006-09 (E)

Calculation of load capacity of spur and helical gears - Part 3: Calculation of tooth bending strength

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	1
4	Tooth breakage and safety factors	2
5	Basic formulae	2
5.1	Safety factor for bending strength (safety against tooth breakage), SF	2
5.2	Tooth root stress, F	2
5.3	Permissible bending stress, FP	4
6	Form factor, YF	8
6.1	General	8
6.2	Calculation of the form factor, YF: Method B	9
6.3	Derivations of determinant normal tooth load for spur gears	13
7	Stress correction factor, YS	14
7.1	Basic uses	14
7.2	Stress correction factor, YS: Method B	14
7.3	Stress correction factor for gears with notches in fillets	15
7.4	Stress correction factor, YST, relevant to the dimensions of the standard reference test gears	15
8	Helix angle factor, Y	15
8.1	Graphical value	16
8.2	Determination by calculation	16
9	Rim thickness factor, YB	16
9.1	Graphical values	16
9.2	Determination by calculation	17
10	Deep tooth factor, YDT	18
10.1	Graphical values	18
10.2	Determination by calculation	18
11	Reference stress for bending	19
11.1	Reference stress for Method A	19
11.2	Reference stress, with values F_{lim} and F_E for Method B	19
12	Life factor, YNT	19
12.1	Life factor, YNT: Method A	19
12.2	Life factor, YNT: Method B	19
13	Sensitivity factor, YT, and relative notch sensitivity factor, $Y_{rel T}$	21
13.1	Basic uses	21

13.2	Determination of the sensitivity factors	21
13.3	Relative notch sensitivity factor, Y rel T: Method B	22
14	Surface factors, YR, YRT, and relative surface factor, YR rel T	27
14.1	Influence of surface condition	27
14.2	Determination of surface factors and relative surface factors	28
14.3	Relative surface factor, YR rel T: Method B	28
15	Size factor, YX	30
15.1	Size factor, YX: Method A	30
15.2	Size factor, YX: Method B	30
Annex A (normative) Permissible bending stress, FP, obtained from notched, flat or plain polished test pieces		33
Annex B (informative) Guide values for mean stress influence factor, YM		40
Bibliography		42