ISO 10303-224:2006-08 (E)

Industrial automation systems and integration - Product data representation and exchange - Part 224: Application protocol: Mechanical product definition for process planning using machining features

Contents

Page

1 Scope 1

2 Normative references 2

3 Terms, definitions, and abbreviations 4
3.1 Terms defined in ISO 1101 4
3.2 Terms defined in ISO 5459 4
3.7 Other definitions 5
3.8 Abbreviations 6

4 Information requirements 6
4.1 Units of functionality 7
4.1.1 design_exception 8
4.1.2 feature_definition_item 8
4.1.3 feature_profile 10
4.1.4 library_reference 10
4.1.5 manufacturing_feature 11
4.1.6 manufacturing_part_properties 14
4.1.7 manufacturing_process_control_documentation 15
4.1.8 manufacturing_process_requirement_documents 16
4.1.9 measurement_limitations 16
4.1.10 part_administration_data 18
4.1.11 part_model 18
4.1.12 requisitions 19
4.1.13 shape_representation_for_machining 19
4.2 Application objects 20
4.3 Application assertions 202

5 Application interpreted model 247
5.1 Mapping specification 247
5.1.1 design_exception UoF 248
5.1.2 feature_definition_item UoF 252
5.1.3 feature_profile UoF 296
5.1.4 library_reference UoF 335
5.1.5 manufacturing_feature UoF 342
5.1.6 manufacturing_part_properties UoF 544
5.1.7 manufacturing_process_control_documentation UoF 554
5.1.8 manufacturing_process_requirement_documents UoF 562
5.1.9 measurement_limitations UoF 565
5.1.10 part_administration_data UoF 609
5.1.11 part model UoF 612
5.1.12 requisitions UoF 623
5.1.13 shape_representation_for_machining UoF 626
5.2 AIM EXPRESS short listing 642

6 Conformance requirements 706

Annex A (normative) AIM EXPRESS expanded listing 708

Annex B (normative) AIM short names 894

Annex C (normative) Implementation method specific requirements 907

Annex D (normative) Protocol Implementation Conformance Statement (PICS) proforma 908

Annex E (normative) Information object registration 909

Annex F (informative) Application activity model 910

Annex G (informative) Application reference model 935

Annex H (informative) AIM EXPRESS-G 966

Annex J (informative) Computer interpretable listings 997

Annex K (informative)Technical discussions 998

Bibliography 1005

Figures Figure 1 -- Data planning model xii

Figure 2 -- Angle_taper 21

Figure 3 -- Angular_dimension_tolerance 22

Figure 4 -- Angular_size_dimension_tolerance 23

Figure 5 -- Angularity_tolerance for a plane surface 24

Figure 6 -- Angularity_tolerance for an axis 25

Figure 7 -- Bevel_gear 27

Figure 8 -- Bevel_gear with shaft angle, and pitch angle 27

Figure 9 -- Bevel_gear with root_angle and tip_angle 28

Figure 10 -- Block_base_shape 29

Figure 11 -- Catalogue_gear 32

Figure 12 -- Catalogue_knurl 33

Figure 13 -- Catalogue_marking 34

Figure 14 -- Catalogue_thread 34

Figure 15 -- Chamfer 35

Figure 16 -- Circular_boss 37

Figure 17 -- Circular_boss with taper 37

Figure 18 -- Circular_closed_profile 38

Figure 19 -- Circular_offset_pattern 40

Figure 20 -- Circular_omit_pattern 41

Figure 21 -- Circular_pattern with rotation 42

Figure 22 -- Circular_pattern without rotation 42
Figure 23 -- Circular_runout_tolerance 44
Figure 24 -- Circularity_tolerance 45
Figure 25 -- Complete_circular_path 46
Figure 26 -- Compound_feature 47
Figure 27 -- Concentricity_tolerance 49
Figure 28 -- Conical_hole_bottom 50
Figure 29 -- Constant_radius_edge_round 51
Figure 30 -- Constant_radius_fillet 52
Figure 31 -- Counterbore_hole 53
Figure 32 -- Countersunk_hole 54
Figure 33 -- Curved_dimension_tolerance 55
Figure 34 -- Cutout 57
Figure 35 -- Cylindrical_base_shape 58
Figure 36 -- Cylindricity_tolerance 59
Index 1006
Figure 37 -- Defined_marking 61
Figure 38 -- Defined_thread 62
Figure 39 -- Diagonal_knurl 65
Figure 40 -- Diameter_dimension_tolerance 66
Figure 41 -- Diameter_taper 66
Figure 42 -- Diamond_knurl 67
Figure 43 -- Distance_along_curve_tolerance 70
Figure 44 -- Edge_round 71
Figure 45 -- Fillet 76
Figure 46 -- Flat_hole_bottom 77
Figure 47 -- Flat_slot_end_type 78
Figure 48 -- Flatness_tolerance 79
Figure 49 -- Gear face_width 81
Figure 50 -- Gear nominal_tooth_depth 81
Figure 51 -- Gear profile_shift 82

Figure 52 -- Gear reference_pressure_angle 83

Figure 53 -- Gear root_fillet_radius 83

Figure 54 -- Gear tip_diameter 84

Figure 55 -- General_boss 84

Figure 56 -- General_closed_profile 85

Figure 57 -- General_open_profile 86

Figure 58 -- General_outside_profile 87

Figure 59 -- General_path 88

Figure 60 -- General_pattern 88

Figure 61 -- General_pocket 90

Figure 62 -- General_removal_volume 91

Figure 63 -- General_revolution for an outer shape 92

Figure 64 -- General_revolution for a volume removal 93

Figure 65 -- Groove 96

Figure 66 -- Helical_gear 98

Figure 67 -- Helical_gear left_or_right_hand_tooth 99

Figure 68 -- Helical_gear reference_helix_angle 99

Figure 69 -- Implicit_base_shape_representation 100

Figure 70 -- Knurl 102

Figure 71 -- Linear_path 104

Figure 72 -- Linear_profile 105

Figure 73 -- Linear_profile_tolerance 106

Figure 74 -- Location_dimension_tolerance 106

Figure 75 -- Manufactured_assembly and Mating_definition 109

Figure 76 -- Ngon_base_shape 115

Figure 77 -- Ngon_profile 117

Figure 78 -- Open_slot_end_type 120

Figure 79 -- Outer_diameter 122

Figure 80 -- Outer_diameter_to_shoulder 123

Figure 81 -- Parallelism_tolerance for a plane 124

Figure 82 -- Parallelism_tolerance for an axis 125

Figure 83 -- Partial_circular_path 130

Figure 84 -- Partial_circular_profile 131

Figure 85 -- Perpendicularity_tolerance for a plane 133

Figure 86 -- Perpendicularity_tolerance for a axis 133

Figure 87 -- Planar_face 137

Figure 88 -- Planar_pocket_bottom_condition 142

Figure 89 -- Position_tolerance 143

Figure 90 -- Protrusion 150

Figure 91 -- Radial_dimension_tolerance 150

Figure 92 -- Radiused_slot_end_type 151

Figure 93 -- Recess 152

Figure 94 -- Rectangular_boss 153

Figure 95 -- Rectangular_closed_pocket 154

Figure 96 -- Rectangular_closed_profile 155

Figure 97 -- Rectangular_offset_pattern 156

Figure 98 -- Rectangular_omit_pattern 157

Figure 99 -- Rectangular_open_pocket 158

Figure 100 -- Rectangular_pattern 159

Figure 101 -- Revolved_flat 164

Figure 102 -- Revolved_round 165

Figure 103 -- Rib_top 166

Figure 104 -- Round_hole 167

Figure 105 -- Rounded_end 168

Figure 106 -- Rounded_U_profile 170

Figure 107 -- Shape_profile 172

Figure 108 -- Slot 175

Figure 109 -- Spherical_cap 177

Figure 110 -- Spherical_hole_bottom 178

Figure 111 -- Spur_gear 179

Figure 112 -- Square_U_profile 179

Figure 113 -- Step 181

Figure 114 -- Straight_knurl 182

Figure 115 -- Straightness_tolerance 183

Figure 116 -- Surface_profile_tolerance 184

Figure 117 -- Symmetry_tolerance 185

Figure 118 -- Tee_profile 188

Figure 119 -- Thread 190

Figure 120 -- Through_bottom_condition 193

Figure 121 -- Total_runout_tolerance 197

Figure 122 -- Turned_knurl 198

Figure 123 -- Vee_profile 200

Figure 124 -- Woodruff_slot_end_type 202

Figure F.1 -- IDEF0 basic notation 910

Figure F.2 -- Mechanical products definition for process planning using machining features 921

Figure F.3 -- A0 manufacture mechanical parts 922

Figure F.4 -- A1 manage manufacturing process 923

Figure F.5 -- A13 manage equipment and materials 924

Figure F.6 -- A131 manage inventory 925

Figure F.7 -- A2 capture digital product definition 926

Figure F.8 -- A21 capture part data definition 927

Figure F.9 -- A214 create part model 928

Figure F.10 -- A3 generate manufacturing data 929

Figure F.11 -- A31 generate process plan 930

Figure F.12 -- A311 define resources 931

Figure F.13 -- A312 define operator data 932

Figure F.14 -- A315 define machine instructions 933

Figure F.15 -- A4 operate shop floor 934

Figure G.1 -- ARM EXPRESS-G diagram 1 of 30 936

Figure G.2 -- ARM EXPRESS-G diagram 2 of 30 937

Figure G.3 -- ARM EXPRESS-G diagram 3 of 30 938

Figure G.4 -- ARM EXPRESS-G diagram 4 of 30 939

Figure G.5 -- ARM EXPRESS-G diagram 5 of 30 940

Figure G.6 -- ARM EXPRESS-G diagram 6 of 30 941

Figure G.7 -- ARM EXPRESS-G diagram 7 of 30 942

Figure G.8 -- ARM EXPRESS-G diagram 8 of 30 943

Figure G.9 -- ARM EXPRESS-G diagram 9 of 30 944

Figure G.10 -- ARM EXPRESS-G diagram 10 of 30 945

Figure G.11-- ARM EXPRESS-G diagram 11 of 30 946

Figure G.12 -- ARM EXPRESS-G diagram 12 of 30 947

Figure G.13 -- ARM EXPRESS-G diagram 13 of 30 948

Figure G.14 -- ARM EXPRESS-G diagram 14 of 30 949

Figure G.15 -- ARM EXPRESS-G diagram 15 of 30 950

Figure G.16 -- ARM EXPRESS-G diagram 16 of 30 951

Figure G.17-- ARM EXPRESS-G diagram 17 of 30 952

Figure G.18 -- ARM EXPRESS-G diagram 18 of 30 953

Figure G.19 -- ARM EXPRESS-G diagram 19 of 30 954

Figure G.20 -- ARM EXPRESS-G diagram 20 of 30 955

Figure G.21 -- ARM EXPRESS-G diagram 21 of 30 956

Figure G.22 -- ARM EXPRESS-G diagram 22 of 30 957

Figure G.23 -- ARM EXPRESS-G diagram 23 of 30 958

Figure G.24 -- ARM EXPRESS-G diagram 24 of 30 959

Figure G.25 -- ARM EXPRESS-G diagram 25 of 30 960

Figure G.26 -- ARM EXPRESS-G diagram 26 of 30 961

Figure G.27 -- ARM EXPRESS-G diagram 27 of 30 962

Figure G.28 -- ARM EXPRESS-G diagram 28 of 30 963

Figure G.29 -- ARM EXPRESS-G diagram 29 of 30 964

Figure G.30 -- ARM EXPRESS-G diagram 30 of 30 965

Figure H.1 -- application context -- AIM EXPRESS-G diagram 1 of 30 967

Figure H.2 -- product definition -- AIM EXPRESS-G diagram 2 of 30 968

Figure H.3 -- property definition -- AIM EXPRESS-G diagram 3 of 30 969

Figure H.4 -- representation -- AIM EXPRESS-G diagram 4 of 30 970

Figure H.5 -- shape_representation -- AIM EXPRESS-G diagram 5 of 30 971

Figure H.6 -- shape_aspect -- AIM EXPRESS-G diagram 6 of 30 972

Figure H.7 -- characterized_object -- AIM EXPRESS-G diagram 7 of 30 973

Figure H.8 -- geometry topology -- AIM EXPRESS-G diagram 8 of 30 974

Figure H.9 -- geometric orientation -- AIM EXPRESS-G diagram 9 of 30 975

Figure H.10 -- curve -- AIM EXPRESS-G diagram 10 of 30 976

Figure H.11 -- bounded_curve -- AIM EXPRESS-G diagram 11 of 30 977

Figure H.12 -- surface -- AIM EXPRESS-G diagram 12 of 30 978

Figure H.13 -- bounded_surface -- AIM EXPRESS-G diagram 13 of 30 979

Figure H.14 -- topology -- AIM EXPRESS-G diagram 14 of 30 980

Figure H.15 -- shell -- AIM EXPRESS-G diagram 15 of 30 981

Figure H.16 -- document -- AIM EXPRESS-G diagram 16 of 30 982

Figure H.17 -- approval -- AIM EXPRESS-G diagram 17 of 30 983

Figure H.18 -- person organization -- AIM EXPRESS-G diagram 18 of 30 984

Figure H.19 -- person organization assignment -- AIM EXPRESS-G diagram 19 of 30 985

Figure H.20 -- date -- AIM EXPRESS-G diagram 20 of 30 986

Figure H.21 -- action -- AIM EXPRESS-G diagram 21 of 30 987

Figure H.22 -- security classification -- AIM EXPRESS-G diagram 22 of 30 988

Figure H.23 -- units -- AIM EXPRESS-G diagram 23 of 30 989

Figure H.24 -- measure with unit -- AIM EXPRESS-G diagram 24 of 30 990

Figure H.25 -- measure qualification and datums -- AIM EXPRESS-G diagram 25 of 30 991

Figure H.26 -- tolerances -- AIM EXPRESS-G diagram 26 of 30 992

Figure H.27 -- geometric tolerance -- AIM EXPRESS-G diagram 27 of 30 993

Figure H.28 -- group and identification assignment -- AIM EXPRESS-G diagram 28 of 30 994

Figure H.29 -- externally defined item -- AIM EXPRESS-G diagram 29 of 30 995

Figure H.30 -- attributes -- AIM EXPRESS-G diagram 30 of 30 996

Tables Table B.1 -- AIM short names of entities 894

Table K.1 -- Summary of 3rd edition ARM changes 999

Table K.2 -- Summary of 3rd edition AIM changes 1000

Table K.3 -- Summary of 3rd edition changes for gear entity 1003