

DIN 8902:2020-08 (E)

Pressure resistant circular sight glasses of soda-lime-glass

| Contents | | Page |
|---|---|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Dimensions and designation | 6 |
| 5 | Material | 7 |
| 5.1 | General | 7 |
| 5.2 | Strength | 7 |
| 5.3 | Thermal properties | 7 |
| 5.3.1 | Mean coefficient of linear thermal expansion | 7 |
| 5.3.2 | Allowable minimum/maximum temperature TS | 7 |
| 5.3.3 | Thermal shock endurance | 8 |
| 5.4 | Chemical resistance | 8 |
| 5.5 | Material imperfections | 8 |
| 5.5.1 | Blisters | 8 |
| 5.5.2 | Knots and streaks | 8 |
| 5.5.3 | Crystalline inclusions | 8 |
| 6 | Finish | 9 |
| 7 | Limit dimensions, form and position tolerances, edge conditions | 9 |
| 7.1 | Limit dimensions | 9 |
| 7.2 | Tolerances of form and position | 10 |
| 7.3 | Chamfer on the sight glass | 10 |
| 8 | Testing | 10 |
| 8.1 | General | 10 |
| 8.2 | Thermal shock endurance | 11 |
| 8.3 | Dimensional deviations | 11 |
| 8.4 | Material imperfections | 11 |
| 9 | Marking | 11 |
| 10 | Packaging | 12 |
| 11 | Installation, safety requirements | 13 |
| Annex A (informative) Explanatory notes | | 14 |
| A.1 | Mechanical strength | 14 |
| A.2 | Maximum application temperature | 14 |
| A.3 | Chemical resistance | 15 |
| Bibliography | | 16 |
| Figures Figure 1 -- Schematic diagram of a possible installation of a sight glass | | 6 |

| | |
|---|-----------|
| Figure 2 -- Form and position tolerances, chamfer on a sight glass | 9 |
| Figure 3 -- Spaces for marking | 12 |
| Figure A.1 -- Loss in mass of sight glasses | 15 |
| Tables Table 1 -- Dimensions and maximum allowable pressure | 6 |
| Table 2 -- Permissible frequency of blisters | 8 |
| Table 3 -- Limit dimensions for diameter and thickness | 9 |
| Table 4 -- Flatness, parallelism | 10 |
| Table 5 -- Chamfer on the sight glass | 10 |
| Table 6 -- Dimensions of spaces for marking | 12 |