

# DIN 28086:2022-11 (E)

## Eyelets on apparatuses - Dimensions and maximum loadings

---

### Contents

Page

Foreword .....	3
1 Scope .....	4
2 Normative references .....	4
3 Terms and definitions.....	4
4 Symbols and abbreviations.....	5
5 General .....	6
6 Dimensions, designation.....	6
6.1 General .....	6
6.2 Designation example.....	7
7 Lifting lug arrangement .....	7
8 Maximum lifting capacities .....	9
8.1 General .....	9
8.2 Maximum shackle forces .....	10
8.3 Maximum lifting lug forces.....	10
8.4 Reinforcement plate and throat thicknesses .....	11
8.5 Maximum vessel end load .....	11
9 Material .....	12
10 Welding.....	12
Annex A (informative) Sample calculation.....	13
Bibliography .....	16

### Figures

Figure 1 — Lifting lug .....	6
Figure 2 — Maximum force $F_G = F_L$ for a lifting lug .....	7
Figure 3 — Maximum force $F_G = 2 \cdot F_L$ for two lifting lugs and lifting beam.....	8
Figure 4 — Maximum force $F_G$ for two lifting lugs and a double sling ( $F_L = F_G / (2 \cdot \cos \alpha)$ ) .....	8
Figure 5 — Maximum force $F_G$ for three lifting lugs and a triple sling ( $F_L = F_G / (3 \cdot \cos \alpha)$ ).....	8
Figure 6 — Force coefficient $f$ .....	12
Figure A.1 — Lifting the vessel .....	13

### Tables

Table 1 — Symbols and units.....	5
Table 2 — Lifting lug dimensions .....	7
Table 3 — Maximum shackle force $F_s$ in accordance with DIN 82016 or DIN 82101 <sup>b</sup> .....	9
Table 4 — Maximum forces $F_G$ for various lifting lug arrangements.....	10
Table 5 — Force increase factor $W$ .....	11
Table 6 — Geometric intermediate value $A$ .....	12