DIN 28086:2022-11 (E)

Eyelets on apparatuses - Dimensions and maximum loadings

Contents

Page

Foreword ... 3
1 Scope ... 4
2 Normative references ... 4
3 Terms and definitions ... 4
4 Symbols and abbreviations ... 5
5 General ... 6
6 Dimensions, designation ... 6
6.1 General ... 6
6.2 Designation example ... 7
7 Lifting lug arrangement ... 7
8 Maximum lifting capacities ... 9
8.1 General ... 9
8.2 Maximum shackle forces ... 10
8.3 Maximum lifting lug forces ... 10
8.4 Reinforcement plate and throat thicknesses ... 11
8.5 Maximum vessel end load ... 11
9 Material ... 12
10 Welding ... 12
Annex A (informative) Sample calculation ... 13
Bibliography ... 16

Figures

Figure 1 — Lifting lug ... 6
Figure 2 — Maximum force $F_G = F_L$ for a lifting lug ... 7
Figure 3 — Maximum force $F_G = 2 \cdot F_L$ for two lifting lugs and lifting beam ... 8
Figure 4 — Maximum force F_G for two lifting lugs and a double sling ($F_L = F_G/(2 \cdot \cos \alpha)$) ... 8
Figure 5 — Maximum force F_G for three lifting lugs and a triple sling ($F_L = F_G/(3 \cdot \cos \alpha)$) ... 8
Figure 6 — Force coefficient f ... 12
Figure A.1 — Lifting the vessel ... 13

Tables

Table 1 — Symbols and units ... 5
Table 2 — Lifting lug dimensions ... 7
Table 3 — Maximum shackle force F_S in accordance with DIN 82016 or DIN 82101[b] ... 9
Table 4 — Maximum forces F_G for various lifting lug arrangements ... 10
Table 5 — Force increase factor W ... 11
Table 6 — Geometric intermediate value A ... 12