

# DIN EN 13445-3/A2:2014-03 (E)

## Unfired pressure vessels - Part 3: Design (includes Amendment A2:2013)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Modification to 16.12 .....</b>	<b>4</b>
<b>16.12</b>	<b>Vertical vessels with skirts .....</b>	<b>4</b>
<b>16.12.1</b>	<b>Purpose .....</b>	<b>4</b>
<b>16.12.2</b>	<b>Specific symbols and abbreviations (see Figure 16.12-1, Figure 16.12-2, Figure 16.12-3 and Figure 16.12-4) .....</b>	<b>4</b>
<b>16.12.3</b>	<b>Connection skirt / shell .....</b>	<b>5</b>
<b>16.12.4</b>	<b>Design of skirts without and with openings .....</b>	<b>17</b>
<b>16.12.5</b>	<b>Design of anchor bolts and base ring for skirts .....</b>	<b>20</b>
<b>2</b>	<b>Modification to Clause 22 .....</b>	<b>35</b>
<b>22</b>	<b>Static analysis of tall vertical vessels on skirts .....</b>	<b>35</b>
<b>22.1</b>	<b>Purpose .....</b>	<b>35</b>
<b>22.2</b>	<b>Specific definitions .....</b>	<b>36</b>
<b>22.2.1</b>	<b>Tall vertical vessels .....</b>	<b>36</b>
<b>22.2.2</b>	<b>Dead loads .....</b>	<b>36</b>
<b>22.2.3</b>	<b>Live loads .....</b>	<b>36</b>
<b>22.2.4</b>	<b>Wind loads on columns .....</b>	<b>36</b>
<b>22.2.5</b>	<b>Earthquake loads on columns .....</b>	<b>36</b>
<b>22.2.6</b>	<b>Forces from attached external piping on columns .....</b>	<b>36</b>
<b>22.3</b>	<b>Specific symbols and abbreviations .....</b>	<b>37</b>
<b>22.4</b>	<b>Loads .....</b>	<b>37</b>
<b>22.4.1</b>	<b>Pressures .....</b>	<b>37</b>
<b>22.4.2</b>	<b>Dead loads .....</b>	<b>37</b>
<b>22.4.3</b>	<b>Live loads .....</b>	<b>38</b>
<b>22.4.4</b>	<b>Wind loads .....</b>	<b>38</b>
<b>22.4.5</b>	<b>Earthquake loads .....</b>	<b>40</b>
<b>22.4.6</b>	<b>Additional loads from attached external piping at nozzles and supports .....</b>	<b>40</b>
<b>22.5</b>	<b>Load combinations .....</b>	<b>41</b>
<b>Table 22-1</b>	<b>- Load combinations for columns .....</b>	<b>42</b>
<b>22.6</b>	<b>Stress analysis of pressure vessel shells and skirts .....</b>	<b>43</b>
<b>22.6.1</b>	<b>Cylindrical pressure vessel shells .....</b>	<b>43</b>
<b>22.6.2</b>	<b>Conical sections of the pressure vessel .....</b>	<b>43</b>
<b>22.6.3</b>	<b>Skirt shell .....</b>	<b>43</b>
<b>22.7</b>	<b>Design of joint between skirt and pressure vessel (at dished end or cylindrical shell) .....</b>	<b>43</b>
<b>22.8</b>	<b>Design of anchor bolts and base ring assembly .....</b>	<b>43</b>
<b>22.9</b>	<b>Foundation loads .....</b>	<b>44</b>
<b>Table 22-2</b>	<b>- Data for foundation design .....</b>	<b>44</b>