DIN EN 12953-3:2016-12 (E)

Shell boilers - Part 3: Design and calculation for pressure parts

Contents

Page

European foreword 5

1 Scope 7

2 Normative references 7

3 Terms and definitions 7

4 Symbols and abbreviations 8

5 General 8
5.1 Boilers 8
5.2 Hot-water boilers 8
5.3 Main welds 8
5.4 Weld factor 9
5.5 Thermal design of furnaces tubes 9
5.5.1 Design conditions 9
5.5.2 Furnace dimensions 11
5.5.3 Heat input 11
5.5.4 Additional operating conditions 12
5.6 Dimensions of pressure parts 12
5.7 Determination of pressures 12
5.7.1 Maximum allowable pressure 12
5.7.2 Calculation pressure 12
5.7.3 Safety valves set pressure 12
5.7.4 Hydrostatic test pressure 13
5.8 Allowances 13
5.8.1 Allowance for material supply tolerances and forming processes 13
5.8.2 Allowance for metal wastage 13
5.9 Additional material requirements for plates 13
5.10 Standardized fittings 14
5.11 Flanges 14
5.12 Design by analysis 14
5.13 Economizer and superheater 14

6 Calculation temperature and nominal design stress 14
6.1 Calculation temperature 14
6.2 Nominal design stress 15

7 Cylindrical shells 15
7.1 Shell thickness 15
7.1.1 Requirements 15
7.1.2 Required wall thickness including allowances 16
7.2 Basic calculation subjected to internal pressure 16
7.3 Boiler supports and lifting lugs 16

8 Openings and branches in cylindrical shells 16
8.1 General 16
8.1.1 Introduction 16
8.1.2 Requirements for the reinforcement of openings in shells 16
8.1.3 Effective lengths lrs for calculation of efficiencies and of compensations 18
8.1.4 Condition of isolated openings 22

8.1.5 Requirements for design of branches 22
8.1.6 Requirements for design of reinforcing pads 22
8.1.7 General requirements for calculation of cross-sectional and pressure-loaded areas 23
8.2 Efficiency factor, alternative calculation method, maximum diameter of an un-reinforced opening 23
8.2.1 General 23
8.2.2 Allowable efficiency and maximum diameter of an unreinforced opening 24
8.2.3 Isolated openings 24
8.2.4 Adjacent openings 25
8.3 Design of openings and branches in shells (efficiency and reinforcement) 25
8.3.1 Symbols and abbreviations 25
8.3.2 Requirements for application 26
8.3.3 Design of isolated openings and branch connections 30
8.3.4 Design of adjacent openings and branch connections 32

9 Ends 33
9.1 Unstayed dished heads without openings 33
9.1.1 Unstayed dished heads under internal pressure 33
9.1.2 Limiting conditions 33
9.1.3 Unstayed dished heads under external pressure 35
9.2 Flat unstayed removable closures 36
9.3 Unstayed flat plates 37

10 Supported flat plates, stays and stiffeners 38
10.1 Breathing space for flat plates 38
10.2 Stayed flat surfaces 40
10.2.1 General 40
10.2.2 Radius of flange 40
10.2.3 Point of support 40
10.2.4 Thickness 41
10.2.5 Values of constant C4 44
10.2.6 Stays for wet back reversal chambers 54
10.2.7 Stay tubes and bars 56
10.2.8 Loads on stay tubes and bar stays 56
10.2.9 Gusset stays 56
10.2.10 Weld attachments 58
10.2.11 Additional requirements for set-in end plates 58
10.2.12 Girder stays supporting the flat section of a reversal chamber 60

11 Design of isolated openings in boiler flat end plates 60
11.1 Unreinforced isolated openings 60
11.2 Branch openings 60
11.3 Manholes, headholes and handholes 62

12 Unpierced tubes and tube plates 63
12.1 Thickness of straight tubes subject to external pressure 63
12.2 Thickness of straight tubes subject to internal pressure 64
12.3 Wall thickness and ovality of elbows and tube bends 64
12.3.1 General 64
12.3.2 Departure from circularity of the tube bends 64
12.4 Smoke tubes 66
12.5 Pitch of tubes 70
12.6 Thickness of the tube plates within tube nests 70

13 Furnaces tubes, furnace components and reversal chambers of cylindrical form subject to external pressure 71
13.1 Furnaces tubes 71
13.1.1 Plain furnaces tubes 71
13.1.2 Corrugated furnaces tubes 71
13.1.3 Safety factors 72
13.1.4 Furnace components 72
13.1.5 Reversal chambers 72

13.2 Calculation length of composite furnaces tubes 73
13.3 Tolerances of furnaces tubes 74
13.4 Stiffeners 74
13.4.1 General 74
13.4.2 Stiffener sections made from bar or plate 75
13.4.3 Stiffeners located within the zone of peak heat flux 75
13.4.4 Bowling hoops 75

14 Access and inspection openings 78
14.1 General requirements 78
14.2 Types and minimum dimensions of access and inspection openings 79
14.3 Minimum gasket bearing width and clearance for access and inspection doors 81
14.4 Access and inspection openings in flat plates 81
14.5 Requirements for entry area into boilers with a shell outside diameter greater than 1 400 mm 81
14.6 Accessibility and arrangement of entry and inspection openings 81

Annex A (informative) Calculation form for "Walker"-type reverse curve sections or corrugations 82

Annex B (normative) Furnace calculation temperature 84

B.1 Calculation of the maximum and the middle furnace wall temperature 84

Annex C (informative) Calculation of tube plate temperatures 87

C.1 General 87
C.2 Symbols 87
C.3 Calculation method 88
C.3.1 Radiation coefficients 88
C.3.2 Convection coefficients 92
C.3.3 Weighted average gas-side heat transfer coefficient 95
C.3.4 Tube plate thermal conductance 97
C.3.5 Water side heat transfer 98
C.3.6 Tube plate temperatures 98
C.4 Example of a calculation carried out using the method given in C.3 101
C.4.1 Design data assumed 101
C.4.2 Calculation of radiation coefficient 102
C.4.3 Calculation of convection coefficients 102
C.4.4 Calculation of weighted average gas-side heat transfer coefficient 102
C.4.5 Calculation of tube plate thermal conductance 102
C.4.6 Calculation of tube plate temperatures 103

Annex D (normative) Economizer and superheater with water tube design connected to the shell boiler 104

D.1 General 104
D.2 Design of economizer and superheater connected to shell boilers 104

Annex E (informative) Significant technical changes between this European Standard and the previous edition 106

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2014/68/EU aimed to be covered 107

Bibliography 108