

# DIN 6647-3:2020-07 (E)

## Means of package - Cylindrical beverage containers - Part 3: Allowable operating pressure up to 0,3 MPa, nominal volume greater 100 l

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		4
1 <b>Scope</b> .....		5
2 <b>Normative references</b> .....		5
3 <b>Terms and definitions</b> .....		6
4 <b>General requirements</b> .....		7
5 <b>Technical requirements</b> .....		7
5.1 <b>Design and surface finishes</b> .....		7
5.2 <b>Safety equipment</b> .....		8
5.3 <b>Insulation</b> .....		8
5.4 <b>Containers without internal liners</b> .....		8
5.5 <b>Containers with internal liners</b> .....		9
6 <b>Hygienic requirements</b> .....		9
7 <b>Testing</b> .....		10
8 <b>Marking</b> .....		10
9 <b>Documentation</b> .....		11
Bibliography .....		12
Figures Figure 1 -- Containers as covered by the PED, Annex II, diagram 2 .....		4
Figure 2 -- Vertical container .....		6
Figure 3 -- Horizontal container .....		6
Figure 4 -- Safety valve .....		8
Figure 5 -- Flow path with baffle plate .....		9
Figure 6 -- Push-in tap with outlet tube .....		10