

DIN EN 1254-8:2021-10 (E)

Copper and copper alloys - Plumbing fittings - Part 8: Press fittings for use with plastics and multilayer pipes

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	7
3	Terms and definitions	9
4	Product characteristics	9
4.1	Internal pressure	9
4.2	Tightness	9
4.3	Resistance to high temperature for fittings with elastomeric seals (for heating networks)	10
4.4	Release of dangerous substances	11
4.5	Durability	11
4.6	Wall thickness at threaded portions of adaptor fittings	12
4.7	Dimensions of tail pipe ends for swivel fittings	12
4.8	Dimensions of gas union connectors	12
4.9	Threaded end dimensions	12
4.10	Other adapter ends (not defined in EN 1254-20:2021)	12
4.11	Bore dimensions	12
4.12	Identity of elastomeric sealing material for liquid applications	12
4.13	Identity of elastomeric sealing material for gas applications	13
4.14	Pipe abutment	13
4.15	Alignment of the fitting ends	13
4.16	Shapes for tightening systems	13
4.17	Surface condition	13
4.18	Plated or coated surfaces	13
4.19	Internal support	13
5	Testing, assessment and sampling methods	13
5.1	General	13
5.2	Internal pressure	14
5.3	Tightness	15
5.4	Durability	18
5.5	Wall thickness at threaded portions of adaptor fittings	19
5.6	Dimensions of tail pipe ends for swivel fittings	19
5.7	Dimensions of gas union connectors	20
5.8	Threaded end dimensions	20
5.9	Bore dimensions	20
5.10	Identity of elastomeric sealing material for liquid applications	20
5.11	Identity of elastomeric sealing material for gas applications	20
5.12	Alignment of the fitting ends	20
6	Evaluation of conformity	20
6.1	General	20
6.2	Type testing	21
6.3	Factory production control (FPC)	26
7	Designation	30

8	Marking, labelling and packaging	30
8.1	General	30
8.2	Additional marking	30
8.3	Dezincification resistant copper zinc alloys	31
	Bibliography	32