

DIN EN 12952-3:2023-01 (Englisc h)

Water-tube boilers and auxiliary installations - Part 3: Design and calculation for pressure parts of the boiler

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 8 |
| 1 | Scope | 10 |
| 2 | Normative references | 10 |
| 3 | Terms and definitions | 11 |
| 4 | Symbols and abbreviations | 11 |
| 5 | General | 11 |
| 5.1 | Purpose | 11 |
| 5.2 | Dimensions of pressure parts | 11 |
| 5.3 | Strength of pressure parts | 12 |
| 5.4 | Design by analysis | 12 |
| 5.5 | Cyclic loading | 12 |
| 5.6 | Other design requirements | 13 |
| 5.6.1 | General | 13 |
| 5.6.2 | Access | 14 |
| 5.6.3 | Drainage and venting | 14 |
| 5.7 | Design, calculation and test pressures | 14 |
| 5.7.1 | Design pressure | 14 |
| 5.7.2 | Calculation pressure | 14 |
| 5.7.3 | Calculation pressure for pressure differences | 15 |
| 5.7.4 | Hydrostatic test | 15 |
| 5.8 | Metal wastage | 16 |
| 5.8.1 | Internal wastage | 16 |
| 5.8.2 | External wastage | 16 |
| 5.8.3 | Requirements | 16 |
| 5.8.4 | Stress corrosion | 16 |
| 5.8.5 | Mechanical requirements | 17 |
| 5.9 | Attachment on pressure parts | 17 |
| 5.9.1 | Load carrying attachments | 17 |
| 5.9.2 | Non load carrying attachments | 17 |
| 6 | Calculation temperature and nominal design stress | 17 |
| 6.1 | Calculation temperature | 17 |
| 6.1.1 | General | 17 |
| 6.1.2 | Circulation boilers | 18 |
| 6.1.3 | Once-through boilers, superheaters and reheaters | 18 |
| 6.1.4 | Hot water generators | 18 |
| 6.1.5 | Temperature allowances for unheated components | 18 |
| 6.1.6 | Headers | 19 |
| 6.1.7 | Unheated components | 19 |
| 6.1.8 | Components protected against radiation | 19 |
| 6.1.9 | Components heated by convection | 19 |
| 6.1.10 | Components heated by radiation | 20 |
| 6.2 | Maximum through-the-wall temperature difference and maximum flue gas temperature for heated drums and headers | 21 |
| 6.2.1 | Maximum through-the-wall temperature difference | 21 |
| 6.2.2 | Headers exposed to flue gas | 21 |

| | | |
|-------|--|----|
| 6.2.3 | Allowable deviations | 22 |
| 6.3 | Design stress | 22 |
| 6.3.1 | General | 22 |
| 6.3.2 | Rolled and forged steels | 23 |
| 6.3.3 | Austenitic steels | 23 |
| 6.3.4 | Non-alloy and low-alloy cast steel | 24 |
| 6.3.5 | Nodular graphite cast iron | 24 |
| 6.3.6 | Design stress for welded connections operating under creep condition | 25 |
| 6.3.7 | Design stress for test pressure | 25 |
| 7 | Cylindrical shells of drums and headers under internal pressure | 25 |
| 7.1 | Shell thickness | 25 |
| 7.1.1 | Requirements | 25 |
| 7.1.2 | Required wall thickness including allowances | 26 |
| 7.2 | Basic calculation | 26 |
| 7.2.1 | Required wall thickness without allowances | 26 |
| 7.2.2 | Different thickness | 26 |
| 7.2.3 | Fabrication tolerances | 26 |
| 7.3 | Combined stress in drum or header shells | 27 |
| 7.3.1 | General | 27 |
| 7.3.2 | Stress from longitudinal loads | 27 |
| 7.3.3 | Longitudinal bending stress | 28 |
| 7.3.4 | Evaluation of ligament stress for inclined ligaments in drums | 29 |
| 7.4 | Boiler drum supports | 30 |
| 7.5 | Other stresses in cylindrical shells | 31 |
| 8 | Openings and branches in cylindrical shells of drums and headers and integral tubes ... | 31 |
| 8.1 | General | 31 |
| 8.1.1 | Requirements for the ligament efficiency of the main body with openings and branches . | 31 |
| 8.1.2 | Effective lengths for calculation of efficiencies of components | 36 |
| 8.1.3 | Conditions for isolated openings | 37 |
| 8.1.4 | Requirements for design of branches | 37 |
| 8.1.5 | Requirements for the design of reinforcing pads | 38 |
| 8.2 | Efficiency factor, calculation by way of approximation, and maximum diameter of unreinforced openings | 38 |
| 8.2.1 | General | 38 |
| 8.2.2 | Allowable efficiency and maximum diameter of unreinforced opening | 38 |
| 8.2.3 | Isolated openings | 39 |
| 8.2.4 | Adjacent openings | 41 |
| 8.3 | Design of openings and branches in cylindrical shells (efficiency and reinforcement) | 42 |
| 8.3.1 | Symbols and abbreviations | 42 |
| 8.3.2 | Requirements for application | 42 |
| 8.3.3 | Design of isolated openings and branch connections | 47 |
| 8.3.4 | Design of adjacent openings and branch connections | 50 |
| 8.4 | Bolted connections | 51 |
| 8.4.1 | General | 51 |
| 8.4.2 | Symbols and abbreviations | 52 |
| 8.4.3 | Calculation of bolt diameter | 53 |
| 8.4.4 | Calculation of bolt load | 54 |
| 8.4.5 | Calculation temperature t_c | 56 |
| 8.4.6 | Design strength value K | 57 |
| 8.4.7 | Safety factor S | 57 |
| 8.4.8 | Quality factor q | 57 |
| 8.5 | Screwed and socket welded connections | 58 |
| 8.5.1 | Screwed connections into the belt | 58 |
| 8.5.2 | Screwed socket connections | 58 |
| 8.5.3 | Socket welded connections | 59 |
| 9 | Headers and plain tubes of rectangular section | 60 |
| 9.1 | General | 60 |
| 9.2 | Symbols and abbreviations | 62 |
| 9.3 | Required wall thickness | 63 |

| | | |
|--------|--|----|
| 9.3.1 | General | 63 |
| 9.3.2 | Minimum wall thickness at the centre of one side | 64 |
| 9.3.3 | Minimum wall thickness at the corners | 64 |
| 9.3.4 | Minimum thickness at a line of openings | 64 |
| 9.3.5 | Minimum wall thickness at staggered opening arrangement (diagonal pitch) | 65 |
| 9.3.6 | Minimum wall thickness at isolated openings | 65 |
| 10 | Ends and spherical shells | 66 |
| 10.1 | Symbols and abbreviations | 66 |
| 10.2 | Spherical shells and dished heads | 66 |
| 10.2.1 | General | 66 |
| 10.2.2 | Calculation formula | 68 |
| 10.2.3 | Openings in dished ends and spherical ends | 71 |
| 10.3 | Unstayed flat ends | 75 |
| 10.3.1 | General | 75 |
| 10.3.2 | Thickness of circular unstayed flat ends | 78 |
| 10.3.3 | Thickness of non-circular and rectangular unstayed flat ends | 78 |
| 10.4 | Flat unstayed closures | 81 |
| 11 | Tubes | 83 |
| 11.1 | Symbols and abbreviations | 83 |
| 11.2 | Thickness of straight boiler tubes | 83 |
| 11.2.1 | Required wall thickness with allowances | 83 |
| 11.2.2 | Required wall thickness without allowances | 84 |
| 11.2.3 | Minimum thickness | 84 |
| 11.2.4 | Circumferentially butt welded tubes | 85 |
| 11.3 | Thickness of tube bends and elbows | 85 |
| 11.3.1 | General | 85 |
| 11.3.2 | Required wall thickness with allowances | 85 |
| 11.3.3 | Required wall thickness without allowances | 86 |
| 11.3.4 | Departure from circularity of tube bends | 86 |
| 11.4 | Flexibility of integral tubing systems | 87 |
| 11.4.1 | General | 87 |
| 11.4.2 | Analysis | 87 |
| 11.5 | Structural attachments to tubes | 87 |
| 11.5.1 | General | 87 |
| 11.5.2 | Attachments welded on tube bends | 89 |
| 11.5.3 | Length of attachments | 89 |
| 11.5.4 | Limit of intensity in the case of radial loading | 89 |
| 11.5.5 | Calculation of intensity in the case of radial loading | 89 |
| 11.5.6 | Strength of welds | 91 |
| 11.6 | Fitting and joining of heated tubes | 92 |
| 11.6.1 | Fitting of tubes | 92 |
| 11.6.2 | Joining of heated tubes | 92 |
| 11.7 | Joining of unheated tubes | 92 |
| 11.7.1 | General | 92 |
| 11.7.2 | Flanges and bolting | 92 |
| 11.7.3 | Butt welded joints | 92 |
| 11.7.4 | Screwed or screwed and seal welded joints | 92 |
| 11.8 | Standardized fittings | 92 |
| 12 | Pressure parts of irregular shape | 93 |
| 12.1 | Hydrostatic test for determining the allowable internal pressure | 93 |
| 12.1.1 | General | 93 |
| 12.1.2 | Proof test to produce yielding | 93 |
| 12.1.3 | Proof test to destruction | 94 |
| 12.2 | Numerical methods | 94 |
| 12.2.1 | General | 94 |
| 12.2.2 | Methods | 94 |
| 12.2.3 | Evaluation of stress | 95 |
| 13 | Fatigue | 95 |

| | | |
|--|---|-----|
| 13.1 | General | 95 |
| 13.1.1 | Procedure | 95 |
| 13.1.2 | Fatigue loading | 95 |
| 13.1.3 | Calculation of fluctuating stress | 96 |
| 13.1.4 | Fatigue assessment | 96 |
| 13.2 | Symbols and abbreviations | 96 |
| 13.3 | Exemption rule for fatigue analysis | 98 |
| 13.3.1 | General | 98 |
| 13.3.2 | Materials | 98 |
| 13.3.3 | Loadings | 99 |
| 13.3.4 | Temperature differences during transient operating conditions | 100 |
| 13.4 | Stress analysis for fatigue calculation | 106 |
| 13.4.1 | Principal and equivalent stresses | 106 |
| 13.4.2 | Temperature of a load cycle | 106 |
| 13.4.3 | Protection of the magnetite layer | 107 |
| 13.4.4 | Allowable circumferential stress range at the inside corner of a bore | 107 |
| 13.4.5 | Circumferential stress caused by pressure at the inside corner of a bore | 107 |
| 13.4.6 | Stresses on the branch caused by external forces and moments | 108 |
| 13.4.7 | Thermal stresses | 108 |
| 13.4.8 | Upper and lower limit of the circumferential stress at the inside corner of a bore | 108 |
| 13.4.9 | Admissible through-the-wall temperature differences | 112 |
| 13.4.10 | Allowable temperature transients | 113 |
| 13.4.11 | Components with oblique and/or non-radial branches | 113 |
| 13.5 | Example calculations | 113 |
| Annex A (normative) Calculation of tube bends and elbows | | |
| A.1 | General | 117 |
| A.2 | Symbols and abbreviations | 117 |
| A.3 | Calculation | 118 |
| A.3.1 | Required wall thickness | 118 |
| A.3.2 | Calculation of the wall thickness | 118 |
| A.3.3 | Calculation of stress | 120 |
| A.3.3.1 | The strength conditions for the intrados of the bend shall be: | 120 |
| A.3.3.2 | The strength conditions for the extrados of the bend shall be: | 120 |
| Annex B (normative) Fatigue cracking - Design to allow for fluctuating stress | | 127 |
| B.1 | General | 127 |
| B.2 | Conditions | 127 |
| B.3 | Symbols and abbreviations | 129 |
| B.4 | Cyclic stress range and mean cyclic stress in the case of uniaxial and multiaxial fluctuating stress | 130 |
| B.4.1 | General | 130 |
| B.4.2 | Uniaxial stress state | 130 |
| B.4.3 | Multiaxial stress state with principal stress directions constant | 130 |
| B.5 | Correction factors for taking into account the influences of surface finish and weldments | 132 |
| B.6 | Controlling stress range | 140 |
| B.6.1 | General | 140 |
| B.6.1.1 | Controlling stress range | 140 |
| B.6.1.2 | Elastic range | 140 |
| B.6.1.3 | Partly elastic range | 140 |
| B.6.1.4 | Fully plastic range | 140 |
| B.6.2 | Correction factor | 141 |
| B.7 | Permissible stress range with a known number of load cycles | 142 |
| Annex C (informative) Examples of calculating the effects of fatigue | | 143 |
| C.1 | General | 143 |

| | | |
|---|--|------------|
| C.2 | Calculation of the admissible number of load cycles | 143 |
| C.3 | Calculation of the admissible temperature gradient | 146 |
| Annex D (informative) Physical properties of steels | | 150 |
| D.1 | General | 150 |
| D.2 | Symbols and abbreviations | 150 |
| D.3 | Physical properties | 150 |
| D.3.1 | Density | 150 |
| D.3.2 | Differential coefficient of linear thermal expansion | 150 |
| D.3.3 | Heat capacity | 151 |
| D.3.4 | Thermal diffusivity | 151 |
| D.3.5 | Poisson's ratio | 151 |
| D.4 | Physical properties of steels | 151 |
| D.4.1 | Data sheet (tables) | 151 |
| D.4.2 | Graphs | 153 |
| D.4.3 | Polynomials | 157 |
| Annex E (informative) Consideration of external wastage due to flue gas exposure | | 160 |
| E.1 | General | 160 |
| E.2 | Symbols and abbreviations | 160 |
| E.3 | Wall thickness of straight tubes in accordance to Clause 11 | 160 |
| E.3.1 | Required wall thickness with allowance | 160 |
| E.3.2 | Required wall thickness without allowances | 160 |
| E.3.3 | Circumferentially butt welded tubes | 160 |
| E.4 | Wall thickness of tube bends and elbows in accordance with Clause 11 | 161 |
| E.4.1 | Required wall thickness with allowance | 161 |
| E.4.2 | Required wall thickness without allowances | 161 |
| E.5 | Wall thickness of tube bends and elbows in accordance with Annex A | 161 |
| Annex F (informative) Significant technical changes between this European Standard and the previous edition | | 162 |
| Annex ZA (informative) Clauses of this European Standard addressing essential safety requirements of the Pressure Equipment Directive 2014/68/EU | | 163 |
| Bibliography | | 165 |